

## Pro330S



### Compact and smart label printer

The OKI Pro330S label printer is the world's smallest\*<sup>1</sup> LED toner color label printer, offering monochrome thermal customers the ability to create versatile and professional color labels and tags that maximize the effectiveness of their print advertising.

The Pro330S can quickly and easily print high-quality full-color labels and tags for a variety of productions, including gift certificates, coupons, value-added receipts, photo ID tags, visitor badges, price and promotional stickers, affixed labels, retail, ribbon or box-attached labels, and more to attract customer interest. With its compact size, the Pro330S can be used anywhere and is easy to transport. You can produce your own unique printed materials in a variety of ways, and your customers can take your products to a new level with their own various advertising campaigns on site.

#### Toner technology that provides print quality

No need for expensive priced inkjet media. Toner method does not bleed into water and offers strength in UV.

#### CMY tri-color integrated toner cartridge

Only one toner is needed to maintain inventory and speed production, simplifying warehousing; the three-color integrated toner can be easily replaced and the equipment can be used quickly without replacement delays.

#### Wired LAN and Wireless LAN

USB cables have always placed the printing PC in the vicinity, making space utilization difficult; OKI's Pro330S connects the Pro330S to the network via a wired LAN or optional wireless LAN, allowing easy printing on various PCs in the network.

#### Easy installation and printing

The Pro330S requires only the installation of a Windows driver to complete the basic environment for use on a PC. A variety of Windows programs, from general labels to variable data labels, allow you to design and print labels easily and quickly.

|  |   |
|--|---|
| Colour/Black and White   | ✓ |
| Width 25-86mm  | ✓ |
| Length 53-551mm  | ✓ |
| Print Speed Max. 152.4mm/S                                     | ✓ |
| Media Recognition: Black marks, holes, notches, gaps, no marks | ✓ |



\*1 Standard for installation area for color LED/laser printers, based on our own research as of September 2021.

# Pro330S | Color Label Printer

| Label Printer       |  |
|---------------------|--|
| Printing method     | Digital 3 LED full color dry type (CMY)  |
| Printing speed      | Max. 152.4mm (6")/sec.                   |
| Time To First Print | 5 sec; in standby (at Cold Start)*1      |
| Warm-up time        | 23 seconds (when power is turned on)     |
| Resolution          | 1200 x1200 dpi                           |
| Memory              | 512 MB                                   |
| Toner cartridge     | Integrated CMY tri-color toner cartridge |

| Interfaces and Software |   |
|-------------------------|---|
| Connection              | High-speed USB 2.0, 10Base-T/100Base-TX Ethernet (basic) IEEE802.11 b / g / n / a wireless LAN (optional)   |
| Printing Language       | PCL6(XL), PCL5c   |
| Networks & Protocols    | TCP/IPv4, TCP/IPv6, NetBIOS over TCP, LPR, Port9100, IPP, FTP, HTTP, TELNET, SMTP, POP3, SNMPv1/v3, DHCP, DHCPv6, DNS, DDNS, UPnP, WINS, Bonjour, SNMP, LLTD, WSD, SSL / TLS, IPsec, IEEE802.1X |
| OS Compatibility        | Windows 8, 8.1, 10<br>Windows Server 2012, 2012 R2, 2016  |

| Font Support |                                     |
|--------------|-------------------------------------|
| Font Support | 4 bitmap fonts<br>27 extended fonts |

| Printer Setup        |  |
|----------------------|--|
| Display              | Mono LCD;16 Characters x2 Line   |
| Environment          | Operating temperature/humidity: 10°C to 32°C (recommended temperature: 17°C to 27°C)/20% to 80% RH (recommended humidity: 50% to 70% RH) |
| Power Supply         | Single phase 220-240VAC, frequency 50/60Hz+/-2%.   |
| Power Consumption    | General: approx. 250 W, standby: 10 W, max: 650 W<br>Power saving: approx. 5 W, sleep mode: approx. 1 W (depending on device settings).  |
| Product size (HxWxD) | 195x198x380mm  |
| Product Weight       | Approx. 9.5 kg   |
| Printer Life         | 120km or 5 years   |





\*1 Time until the edge of the paper comes out of the ejection port after the printing operation is started  
\*2 Available in selected countries only. Please check with your local dealer or contact OKI

**Consumables usage guide:** To protect the printer and to allow for left-transmission capability, this model was designed to work only with authentic OKI toner cartridges. These can be found at OKI's registered trademarks. If you are using other toner cartridges, even if they are listed as "compatible," they may not work at all, and even if they do possibly work, printer performance and print quality may be reduced.

| Paper Management |  |
|------------------|--|
| Width            | 25 - 86mm  |
| Length           | 53 - 551mm   |
| Thickness        | 0.08 - 0.25mm  |
| Media Feeding    | Rolled paper, folding, single sheet                              |
| Mark Type        | Black marks (printed side, back), holes, notches, gaps, no marks |
| Cutter           | Built-in rotary cutter (cutting length 53-551 mm)                |
| Media Sensor     | Transmissive sensor, Reflective sensor                           |

| Option              |   |
|---------------------|---|
| Wireless LAN Module | Modules that connect wirelessly*2   |
| Presenter Device    | A device that allows the presenter device to be stopped at the mouth before the printed paper is completely ejected |

| Option – Roll Paper Holder (Roll Paper Feeding Guide) |   |
|---|---|
| Media Type  | Roll paper, die-cut label roll paper            |
| Width   | 25 - 86mm                                       |
| Roll Outer Diameter                                   | Max. 203.2mm (8 inches)                         |
| Core Inner Diameter                                   | 50.8mm (2 inches) or 76.2mm (3 inches)          |
| Roll Weight   | Max. 2.4 kg                                     |
| Printing Side   | Outside the printing surface only (outer rolls) |
| Size (HxWxD)  | 232x175x311mm                                   |

| Consumables      |   |  |
|------------------|---|--|
| Toner Cartridge* |    | 3-color integrated (CMY): approx. 5,000 sheets   |
| Image drum**     |   | 3-color one-piece type (CMY) about 25,000 sheets |
| Transfer belt**  |  | Approx. 100,000 sheets                           |
| Fuser**          |  | Approx. 100,000 sheets                           |

\* For a 25.4mm (1 inch) square black rectangle printed on 216mm x 58mm paper. Reference values based on our in-house testing.  
\*\* For printing only one sheet of 216mm x 58mm paper at a time. Reference values based on our in-house testing.

## Option - Roll Paper Holder (Roll Paper Feeding Guide)



**Oki Data (Singapore) Pte Ltd**  
438A Alexandra Road,  
#02-11/12, Lift Lobby 3,  
Alexandra Technopark,  
Singapore 119967  
Tel: (65) 6221 3722  
[www.oki.com/sg/printing](http://www.oki.com/sg/printing)

**Oki Data (Singapore) Pte Ltd  
Malaysia Branch Office**  
Suite 21.03, 21st Floor,  
Menara IGB, Mid Valley City,  
59200 Kuala Lumpur, Malaysia  
Tel: (03) 2287 1177  
Tel: 1800 88 1177 (Toll Free)  
Fax: (03) 2287 1166  
[www.oki.com/my/printing](http://www.oki.com/my/printing)

**Oki Systems (Thailand) Ltd**  
1168/63 Lumpini Tower,  
22nd Floor, Rama IV Road.,  
Tungmahamek, Sathorn,  
Bangkok, Thailand 10120  
Tel: (662) 679 9235  
Fax: (662) 679 9243, 45  
[www.oki.com/th/printing](http://www.oki.com/th/printing)

© Copyright 2022 OKI DATA (S) PTE LTD.  
OKI DATA (S) PTE LTD is part of the Oki Electric group of companies.  
Specifications subject to change without notice. Version 1. 8/2022.

Windows, Windows8, Windows8.1, and Windows10 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.  
All other product names and brand names are registered trademarks or trademarks of their respective companies.

**CDG Computer Peripheral and Supplies Ltd.**

244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand  
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990  
[www.cps.co.th](http://www.cps.co.th) • [www.facebook.com/cps.co.th](http://www.facebook.com/cps.co.th)



**OKI**  
Open up your dreams

