



Rich Interface

- Virtual serial port for USB connection
- USB+Serial+Ethernet
- Parallel+USB

HIGH PRINT SPEED (300mm/sec)
INTEGRATED MECHANISM



Integration of mechanism and cutter
150km mechanism lifespan;
1,500,000 times cutter lifespan

TP-3300II Thermal Receipt Printer

INNOVATION, QUALITY *NEW PACKING, A NEW IMAGE*





Specification

| | |
|---------------------|---|
| Print method | Direct thermal |
| Print speed | 300mm/sec. |
| Paper width | 79.5 ± 0.5mm |
| Print width | 64/72mm |
| Interface | USB+Serial+Ethernet, Parallel+USB |
| Wall mount | Support |
| Power | DC24V/2A |
| Reliability | 150km mechanism lifespan; 1,500,000 times cutter lifespan |
| Weight | 1.23kg |
| Dimension | 180.6X139X127MM(LXWXH) |

NEW SIMPLE. BETTER. FASTER Thermal Receipt Printer



TP-3300II



Support 2D Barcode Printing
Integration of mechanism and cutter
300mm/sec ultra high speed

- Compatible with ESC/POS and Star commands
- Waterproof, oil-proof, dust-proof structure
- Kitchen printing and network printing supported
- Network status monitoring, multilink printing supported
- OPOS driver supported
- Printer authentication and software bundle
- High speed driver printing mode, serial port speed is 66% faster
- Auto print recovering when network disconnected
- Virtual serial port for USB connection, USB port supports OPOS application
- 100MB network interface card makes the connection and print much faster; stop receipts misprinting

