

i6310 Enterprise Mobile Computer

The thinnest rugged PDA in the world





High performance

The blazing otca-core 1.4GHz 64-bit processor can run everything you need to take care of business. And with support Android 7.1 and 4+64GB memory, you get superior user experience and investment protection.

Fast data connectivity

802.11 a/b/g/n WiFi 2G/3G/4G Wireless WAN Bluetooth 4.1 BLE

Powerful data collection

2D scan engine 13MP camera get ultra-high resolution photos Accurate location solutions

Highly optimized power system

3.8V, 3800mAh battery ensures long operation hours Pogo pin design for simple and non-intrusive charging

Elegant appearance, Industrial reliability

Stylishness, superior ergonomics for comfort and practical Durability, reliability and productivity IP65 Sealing











SPECIFICATIONS

Basic Characteristics		
CPU	Octa-Core 1.4 Ghz	
RAM	4GB	
ROM	64GB	
O.S	Android 7.1	
Display	5.0 inch TFT-LCD (720 x 1280) color screen	
Dimensions	158mm x 76.2 mm x 13.3mm	
Weight	210g (Battery included)	
Buttons	Volume up/down,Power button,Custom buttons,Scan button,Home,Menu,Back	
Input	Chinese/English, and supports handeriting and soft keyboard	
Barcode Scanner	2D imager	
Main Battery	Rechargeable 3.8V 3800mAhlithium polymer batterry pack(Typical Operation time ≥8 hours)	
RTC Battery	Real time clock battery	

Expansion and peripherals		
Camera	13MP auto-focus color rear camera with flash2MP front-facing camera	
RFID	Supports 13.56Mhz, ISO14443A&B and I SO15693 standard ,Supports NFC	
GPS	GPS,A-GPS, Bei-Dou satellite navigation system,GLONASS	
Sensor	Light sensor,Range sensor, Acceleration sensor,Compass, Gyroscope, Barometer	
Slot	Micro SD/TF×1 ,Micro SIM × 2	
Interfaces	Type-C USB,3.5mm Audio port,POGO PIN	
Audio	Loudspeaker, Microphone, Earpiece	
Fingerprint module	Optional	
Standard	Power adaptor, Data cable, One battery	
Optional	Cradle、Scan Trigger Handle with Charger、Case & Hand strap、Dimensioning Pack	

Radio Communication				
Wi-Fi	802.	802.11 a/b/g/n		
Bluetooth	BT 4	BT 4.1 BLE		
Chinese Version	4G	TDD-LTE(B38/B39/B40/B41) FDD-LTE(B1/B3)		
	3G	TD-SCDMA(B34/B39) WCDMA(B1/B2/B5/B8) CDMA2000 1x EV-DO Rev.A Bc0 800MHz		
	2G	CDMA 1x GSM/EDGE/GPRS(850,900,1800, 1900MHz)		

User Environment		
Operating Temperature	-10~50°c(14~122°F)	
Storage Temperature	-40~70°C(-40~158°F)	
Humidity	5% ~ 95%	
Drop Durability	1.5m	
IP Sealing	65	

Optional Accessory



Scan Trigger Handle with Charger



Case & Hand strap



Dimensioning Pack



Cradle Assembly

