

WORLD CLASS Features
 USER FRIENDLY Price
NISCA PR5300



Specifications

Printing system:	300dpi, 24-bit continuous tone printing, 16.7 million colors
Printing method:	Thermal transfer dye-sublimation
Print media:	PVC or polyester cards with polished PVC finish
Media size:	CR-80: 3.375" x 2.125" / 85.6 x 54mm CR-79: 3.303" x 2.051" / 83.9 x 52.1mm
Media thickness:	.020" (20mil) to .050" (50mil) / .508mm to 1.27mm
Print area:	Edge-to-edge
Input hopper:	100 cards
Exit hopper:	100 cards
Image memory:	8MB with parallel processing, four memory modes
System memory:	2.25MB
Display:	LCD 16 character 2-line display shows printer status and diagnostic prompts
Ribbon types:	YMCKO 250 prints, YMCKOK 210 prints, YMCFK (Ultra Violet) 250 prints, YMC 250 prints, K 1250 prints and BK/OP 250 prints
Print speed :	YMCO: 104 cards / hour YMCO/K: 72 cards / hour YMCKO/K: 66 cards / hour YMCK/K with Lam: 72 cards / hour YMCK with Lam: 84 cards / hour
Encoding:	ISO Standard magnetic stripe w/ dual high- and low-coercivity
Interface:	USB 2.0
Dimensions:	16.57" (h) x 10.66" (w) x 13.03" (d) / 421 x 271 x 331mm
Weight:	26.6 lbs. / 13kg
Operating temp:	65 to 85° F / 18 to 27° C
Power source:	AC power source AC100/240v 50/60Hz auto-switching
Agency listing:	UL: UL1950: UL1950-1993 CE Class B FCC A & B
Operating temp:	65 to 85° F / 18 to 27° C
Drivers:	Windows® compatible
Warranty:	2-year return to depot service printer warranty and 1-year unlimited prints print head warranty.

สนใจติดต่อ: บริษัท คอมพิวเตอร์ เพอร์เฟอรัล แอนด์ ซัพพลายส์ จำกัด
แผนก Auto-ID
 โทร.02-322-9535, 02-722-4040 โทรสาร.02-322-7990