

**CODE SOFT™**



**DP-7645 III**  
Dot Matrix Receipt Printer



**TP-3160**  
Thermal Receipt Printer



**TP-3250I**  
Thermal Receipt Printer



**TP-3250II**  
Thermal Receipt Printer

**CODE SOFT**  
*Receipt Printer*

## General Specification



Model	DP-7645 III	TP-3160	TP-3250I	TP-3250II
Printing method	9-Pin Serial Impact Dot Matrix Printing	Line Thermal Printing		
Printing width	76mm : 400 dots (half dot)	80mm : 72mm / 576 dots & 64mm / 512 dots		
Dot pitch	400 dots / line	576 dots / line & 512 dots / line		
Printing speed	4.5 lines / sec	160mm / sec (42 lines / sec)	250mm / sec (60 lines / sec)	
Number of Columns	76mm : Font A – 33 columns / 35 columns / Font B – 40 columns / 42 columns / Simplified / Traditional Chinese – 21 columns / 22 columns	80mm : Font A – 42 columns / 48 columns / Font B – 56 columns / 64 columns / Simplified / Traditional Chinese – 21 columns / 24 columns		
Character Size	ANK Character Font A : 1.6 x 3.1mm (9 x 9 dots) Font B : 1.2 x 3.1mm (7 x 9 dots) Simplified / Traditional Chinese : 2.7 x 2.7mm (16 x 16 dots)	ANK Character Font A : 1.5 x 3.0mm (12 x 24 dots) Font B : 1.1 x 2.1mm (9 x 17 dots) Simplified / Traditional Chinese : 3.0 x 3.0mm (24 x 24 dots)		
Character table	PC437 / Katakana / PC850 / PC860 / PC863 PC865 / WPC 1252 / PC 866 / PC852c / PC858	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 WPC 1252 / PC 866 / PC852c / PC858 / Latvian / Arabic / PT151, 1251		
Barcode Type	-----	UPC-A/UPC-E/JAN-13/EAN-13/EAN-8/CODABAR/ITF/CODE39/CODE93/CODE128		
Line spacing	4.23mm	3.75mm		
Paper	75.5 +/- 0.5mm @ 75mm	79.5 +/- 0.5mm @ 83mm		
Interface	Parallel / Serial / USB / Ethernet	Parallel / Serial / USB / Wireless	Parallel / Serial / USB / Ethernet	
Input buffer	64K bytes	32K bytes	128K bytes	
NV user memory	-----	60K bytes	256K bytes	
Drawer Kick-Out	DC 12-24V / 1A, 1 Drawer	DC 12-24V / 1A, 2 Drawer		
Power Supply	DC 24V/2.5A	DC 24V/2.5A		
AC adapter	Input : AC 110V / 220V , 50 - 60 Hz Output : DC 24V / 2.5A	Input : AC 110V / 220V , 50 - 60 Hz Output : DC 24V / 2.5A		
Weight	1.60Kg	1.60Kg		
Operating	Temperature : 0°-50° C , Humidity: 10-80 %	Temperature : 0°-45° C , Humidity: 10-80 %		
Storage	Temperature : 0°-60° C , Humidity: 10-90 %	Temperature : 0°-60° C , Humidity: 10-90 %		
Reliability	10 million lines	100KM		
Driver	Win9x / WinXP / Win NT / Win2K / Win Vista	Win9x / WinXP / Win NT / Win2K / Win Vista		
Compatible	ESC / POS	ESC / POS		
Dimension (W*D*H)	149 x 245 x 130 mm	140 x 162 x 140 mm	138 x 194 x 140 mm	137 x 197 x 144 mm
Safety	3C , CE	3C , CE		

All specifications are subject to change without notice

All company and /or product names are trademarks and/or registered trademarks of their respective owners