

The Perfect Compliment for Your Printing Needs

—— Postek R1 External Label Rewinder

The R1 External Rewinder is the perfect compliment to the exceptional performance of Postek's G and T Series Thermal Barcode Label Printers. As a stand-alone product, it is also the perfect compliment to any thermal barcode label printer. The R1 features auto-adaptive torque technology with anti skid functionality, to adjust rewinding speed automatically to a maximum of 8ips. With the R1 working in tandem with a thermal barcode label printer, productivity will be optimized resulting in cost saving efficiencies.

The R1 External Rewinder is yet another example of Postek's customer's needs driven philosophy.



Postek 博思得

Specifications:

R1 Label Rewinder	
Max. Rewinding Speed	8ips (203.2mm/s)
Media Roll	Label width: Max. 120mm Min. 25mm OD 8" (203mm) ID 3" (76.2mm)
Dimensions	L262mm x W220 mm x H232mm
Weight	2.5kgs
Power Rating	12VDC + 5%
Operating Environment	Temperature: 40F - 100F ((0°C - 40°C) Relative humidity: 5% - 85% non condensing

* All specifications are subject to change without notice.**POSTEK ELECTRONICS CO.,LTD.**

Suite 510, Shanghang Building, W. Hongli Road,
Shenzhen, China PC: 518028

Tel: 755-83240988 Fax: 755-83202898

[Http://www.postek.com.cn](http://www.postek.com.cn)