


DIGITAL INSULATION TESTER

MS5203 / MS5203A

MS5203

VOLTAGE AC 750V
DC 1000V

RESISTANCE
200GΩ



EMC
LVD



MS5203A

NEW
MS5203A
DIGITAL IN



VOLTAGE AC 750V
DC 1000V

RESISTANCE
200GΩ



Specifications

MS5203 MS5203A

Output Voltage	Range	Test Current	Accuracy
50V (0~20%)	0~20MΩ	1mA @50K	±(3%+5)
	20~50MΩ		
100V (0~20%)	0~20MΩ	1mA @100K	±(3%+5)
	20~100MΩ		
250V (0~20%)	0~20MΩ	1mA @250K	±(3%+5)
	20~200MΩ		
500V (0~20%)	0~20MΩ	1mA @500K	±(3%+5)
	20~200MΩ		
1000V (0~20%)	200~500MΩ	1mA @1000K	±(3%+5)
	200~1000MΩ		
	1.00~5.00GΩ		
	5.00~10.00GΩ		±(10%+0.2)
DC Voltage Test	200V/1000V		±(0.5%+5)
AC Voltage Test	200V/750V		±(1.5%+5)
Resistance	20Ω/200Ω		±(1%+5)
Continuity Test	0.01~200.0Ω	1mA	±0.5%
		250mA	±0.5%

Specifications

MS5203 MS5203A

Features	MS5203	MS5203A
APO	Auto Power Off	●
LOCK		●
MIN		●
MAX		●
AVG		●
COMP	Compare function	●
TIMER	Timer function	●
MEMO	Store function	●
DAR		●
PASS		●
Backlight		●
REL	Relative Measurement	●
Data Hold		●
LBD	Low Battery Display	●
General		
Power Supply	6×1.5V AA Battery	
Product Size	180mm×140mm×65mm/7.1"×5.5"×2.56"	
Product Weight	922g/2.03lb	
Category	CE CAT III 1000V CAT IV 600V RoHS	