

NS25A

8A - 25A (1/4" - 1")

Standard Model 1/2"-1"

The Mighty Lightweight - weighing in at only 19.8 kg! Built-in safety features, too!

- Motor employs a brake to enhance the safety of the machine.
- Powerful motor completes a thread in only 16 seconds.
- Special bearing used for the main shaft bearing.
- Excellent durability provides improved machine service life and precision.
- Can easily be carried with just one hand!
- New self-opening die head for greater precision.
(notch type NS25AIII only)



PipetoolShop.com

E-mail ; sales@tcgroup.asia



Self-opening die head for NS25A

Manual-opening die head for NS25A



Easy to carry



Cord pocket functions as hand grip, too.





Switch protects die head from touching hand wheel

Standard Accessories:

- Carbon Brushes 2 pair, Cutting Oil (246-R) 0.5 L x 4
- Hex key-wrench 3-5 mm, Dies 1/2"-3/4" 1 set each
- Die head 1/2"-1" one each

รหัสสินค้า	205051
รุ่น	THREADING MACHINE NS25A
ประเภทของหัว	ระบบใช้มือเปิด
ความสามารถ	1/2 ~ 1"
แรงดันไฟฟ้า	220 โวลต์ (50/60 เฮิร์ต)
มอเตอร์	400 วัตต์
ความเร็วของเครื่อง	55 รอบต่อนาที
น้ำหนัก (กก.)	19.8 กิโลกรัม
ขนาด	450 x 320 x 350 มม. (กว้างxยาวxสูง)
อุปกรณ์มาตรฐาน	พื้นตีบสำรอง 2 ชุด, น้ำมัน 1 แกนลอน, กล่องเครื่องมือ 1 ชุด
อุปกรณ์เสริม	สอบถามตัวแทนจำหน่าย REX



Dies Table

ISO 7-1 (JIS B0203) <R> British Standard Pipe Thread: Tapered

BSPT	Tpi	Angle	Width	Alloy	HSS	DH			
1/4" - 3/8"	19	55	27 mm	16P000	160030	295250	295252	295254	290129
1/2" - 3/4"	14	55	27 mm	16P407 *1	166P07	295250	295252	295254	290130
1"	11	55	27 mm	160025 *1	166025	295250	295252	295254	290130



ANSI/ASME B 1.20.1 (American) National Pipe Thread: Tapered

NPT	Tpi	Angle	Width	Alloy	HSS	DH		
1/4" - 3/8"	18	60	27 mm	16P100	166292	295252	295250	290129
1/2" - 3/4"	14	60	27 mm	166721 *3	166731	295252	295250	290128
1"	11.5	60	27 mm	161610 *2	166296	295252	295250	290128



ISO 68-1/261 (JIS B 0205) <M> Metric Thread for Bolt: Parallel

Metric	Pitch	Angle	Width	Alloy	HSS	DH		
M20 P1.5	1.5	60	27 mm	167710	-			

BSB4 British Standard Whitworth for Bolt: Parallel

BSW	Tpi	Angle	Width	Alloy	HSS	DH		
W 3/4	16	55	27 mm	166720 *3	166730	295254		
W 1/2	12	55	27 mm	166721 *3	166731	295254		
W 3/8	11	55	27 mm	166722 *3	166732	295254		
W 1/4	10	55	27 mm	166723 *3	166733	295254		

