

# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

<b>Applicant:</b>	Point Lighting Corporation	<b>Manufacturer:</b>	Point Lighting Corporation
<b>Address:</b>	61 West Dudley Town Road Bloomfield, CT 06002	<b>Address:</b>	61 West Dudley Town Road Bloomfield, CT 06002
<b>Country:</b>	USA	<b>Country:</b>	USA
<b>Contact:</b>	Ryan Pape	<b>Contact:</b>	Ryan Pape
<b>Phone:</b>	860-243-0600	<b>Phone:</b>	860-243-0600
<b>FAX:</b>	860-243-0665	<b>FAX:</b>	860-243-0665
<b>Email:</b>	NA	<b>Email:</b>	NA
<b>Party Authorized To Apply Mark:</b>	Same as Manufacturer		
<b>Report Issuing Office:</b>	Cortland, NY		
<b>Control Number:</b>	<u>3030033</u>	<b>Authorized by:</b>	<i>Catherine Dwyer</i>
			for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
 545 East Algonquin Road, Arlington Heights, IL 60005  
 Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

<b>Standard(s):</b>	Luminaries, UL 1598, 3rd Edition, September 17, 2008, Revisions through and including October 17, 2012; Luminaries, CSA-C22.2 No. 250.0-08, September 17, 2008, General Instruction No.1: 2010, General Instruction No.2: 2012; Supplemental Requirements for Luminaires for Installation on Marine Vessels, UL 1598A, 1st Edition, December 4, 2000, Revisions through and including June 23, 2010; Luminaires for Use in Hazardous (Classified) Locations, UL 844, 13th Edition, January 11, 2006, Revisions through and including June 29, 2012; Electric Luminaries for Use in Hazardous Locations, CSA-C22.2 No. 137-M1981, General Instruction: November 1982, (Reaffirmed 2009)
<b>Product:</b>	LED Light
<b>Models:</b>	Series PRL-97x02-(1 or 2)x-x-xx-xxx, POL-21003-x-(1 or 2)x-xxx-xx and PEL-57003-x-(1 or 2)x-xxx-xx. PRL-97x02-(3,4, 5 or 6)x-x-xx-xxx, POL-21003-x-(3,4, 5 or 6)x-xxx-xx and PEL-57003-x-(3,4, 5 or 6)x-xxx-xx. PRL-97x04-xx-xx-xx-xxx, POL-21004-xx-x-xx-xx-xx, PEL-57004-xx-x-xx-xx-xx, PEL-57005-xx-x-xxx-xx-xx, POL-21005-xx-x-xxx-xx-xx.

**PRODUCT DESCRIPTION**

**PRODUCT COVERED**

LED Light series PRL-97x02-(1 or 2)x-x-xx-xxx, POL-21003-x-(1 or 2)x-xxx-xx and PEL-57003-x-(1 or 2)x-xxx-xx.

For use in the following Hazardous (Classified) Locations:

Class I, Division 2, Groups A, B, C, and D

Class I, Zone 2, Groups IIA, IIB+H2, IIC T6

Temperature Code: T6

Maximum Ambient: 40°C

Marine Outside Type

LED Lights series PRL-97x02-(3,4, 5 or 6)x-x-xx-xxx, POL-21003-x-(3,4, 5 or 6)x-xxx-xx and PEL-57003-x-(3,4, 5 or 6)x-xxx-xx.

For use in the following Hazardous (Classified) Locations:

Class I, Division 2, Groups A, B, C, and D

Class I, Zone 2, Groups IIA, IIB+H2, IIC T6

Temperature Code: T6

Maximum Ambient: 40°C

LED Light series PRL-97x04-xx-xx-xx-xxx, POL-21004-xx-x-xx-xx-xx, and PEL-57004-xx-x-xx-xx-xx.

For use in the following Hazardous (Classified) Locations:

Class I, Division 2, Groups A, B, C, and D

Class I, Zone 2, Groups IIA, IIB+H2, IIC T6

Temperature Code: T6

Maximum Ambient: 55°C

Marine Outside Types

LED Light series POL-21005-xx-x-xxx-xx-xx and PEL-57005-xx-x-xxx-xx-xx.

For use in the following Hazardous (Classified) Locations:

Class I, Division 2, Groups A, B, C, and D

Class I, Zone 2, Groups IIA, IIB+H2, IIC T6

Temperature Code and Maximum Ambient: T5 for -40°C to +55°C and T6 for -40°C to +40°C

Marine Outside Types

**PRODUCT DESCRIPTION**

The products covered are LED luminaries (Recessed and surface / conduit mount obstruction lights) intended for use in Non-Hazardous or Hazardous locations and are intended for installation on branch circuits of 120Vac, 220Vac, 277VAC, 12Vdc, 24Vdc, or 48Vdc. They are suitable for dry, damp or wet locations. The fixtures are Point Obstruction Light (POL), Point Elevated Light (PEL), and Point Rollover Light(PRL). They are all constructed of cast aluminum enclosures and are powder paint coated. They also use all stainless steel hardware.