

# IECEx Certificate of Conformity

### INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx BKI 07.0023	Page 1 of 4	Certificate history

 Status:
 Current
 Issue No: 4
 Issue 3 (2014-10-27)

 Issue 2 (2014-06-16)
 Issue 2 (2014-06-16)

Date of Issue: 2018-01-25 Issue 1 (2011-09-19) Issue 0 (2007-06-05)

Applicant: Cooper Crouse-Hinds GmbH

previously CEAG Sicherheitstechnik GmbH

Neuer Weg Nord 49

D-69412 Eberbach, Germany

Germany

Equipment: Control unit of types

Optional accessory: GHG 44. ....R....

Type of Protection: General requirements, Flameproof enclosures, Increased safety, Intrinsic safety, Encapsulation, Dust

explosion protection - Protection by enclosures

Marking: Ex de ia/ib m [ia/ib] IIC T4...T6

-55 °C ≤ Tamb ≤ +55 °C Ex tD A21 IP66 T 80 °C

for working temperatures see 4.1 of Addendum to IECEx BKI 07.0023

Approved for issue on behalf of the IECEx Edit Molnár

Certification Body:

Position: managing director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.

Certificate issued by:

Testing Station for Explosion Proof Equipment H 1037 BUDAPEST MIKOVINY S.u. 2-4 Hungary





### **IECEx Certificate** of Conformity

Certificate No.: **IECEX BKI 07.0023** Page 2 of 4

Date of issue: 2018-01-25 Issue No: 4

Cooper Crouse-Hinds GmbH Manufacturer:

previously CEAG Sicherheitstechnik GmbH

Neuer Weg Nord 49

D-69412 Eberbach, Germany

Germany

Additional manufacturing

locations:

Cooper Electric (Changzhou) Co. Ltd.

No. 189 Liuyanghe Road

Xinbei District Changzou, Jiangsu China, 213031

China

Eaton Electric (Singapore) PTE Ltd.

100G Pasir Panjang Road

#07-08/#02-09 Interlocal Centre Singapore, 118523

Singapore

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

#### STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2004

Edition:4.0

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

IEC 60079-11:1999

Edition:4

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition:1

IEC 60079-18:1992 Electrical apparatus for explosive gas atmospheres - Part 18: Encapsulation 'm'

IEC 60079-7:2001

Edition:3

Electrical apparatus for explosive gas atmospheres - Part 7: Increased safety 'e'

IEC 61241-0:2004

Edition:1

Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements

IEC 61241-1:2004

Edition:1

Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by enclosures "tD"

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

#### TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

HU/BKI/ExTR07.0022/00

Quality Assessment Reports:

DE/BVS/QAR11.0009/08 GB/BAS/QAR07.0041/07 GB/BAS/QAR11.0007/05



# IECEx Certificate of Conformity

Certificate No.: IECEx BKI 07.0023 Page 3 of 4

Date of issue: 2018-01-25 Issue No: 4

#### EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Control units of type GHG 44. ....R.... consist of a bottom part and a cover with separately approved internal sealing device. They are made of moulded plastic or VA4 sheet steel or light alloy .

See details in addendum to IECEx BKI 07.0023.

SPECIFIC CONDITIONS OF USE: NO



# IECEx Certificate of Conformity

Certificate No.: IECEx BKI 07.0023 Page 4 of 4

Date of issue: 2018-01-25 Issue No: 4

#### **DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

1st issue: new QAR: DE/BVS/QAR11.0009/00

2nd issue:

Additional manufacturing locations:

1.

Cooper Crouse-Hinds PTE Ltd.

No. 2 Serangoon North Avenue, # 06-01 Fu Yu Building, Singapore 554911

SINGAPORE

2.

Cooper Electric (Changzhou) Co. Ltd

No. 189 Liuyanghe Road, Xinbei District, Changzhou, Jiangsu, China 213031

CHINA

Issue 3:

Technical corrections.

See details and correction in the Addendum to 3rd amendment to IECEX BKI 07.0023.

Issue 4:

Change the name and address of the manufacturing location, Singapore

from

 $\hbox{Cooper Crouse-Hinds PTE Ltd., No 2 Serangoon North Avenue 5, \# 06-01, Singapore, 554911 (QAR: GB/BAS/QAR11.0007/04) } \\$ 

to

Eaton Electric (Singapore) PTE Ltd., 100G Pasir Panjang Road,, #07-08/#02-09 Interlocal Centre,, Singapore,118523 (QAR: GB/BAS/QAR11.0007/05)

#### Annexes:

Addendum to 3rd amendment to IECEx BKI 07.0023..pdf Addendum to IECEx BKI 07.0023.pdf

## IEC TECEX

#### ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY

3rd amendmento to IECEx BKI 07.0023

Page 1 of 2

#### 1. Description

Control units of type GHG 44. ....R.... consist of a bottom part and a cover with separately approved internal sealing device. They are made of moulded plastic or VA4 sheet steel or light alloy.

Rail-type webs or top-hat rails have been grooved (plastic enclosure) or riveted (metal enclosure) into the bottom part of the enclosure. They are intended for take up the built-in elements.

Assembling of the control units is permitted.

Attached Ex cable entries has to be covered by separate certificate.

Both variants are suitable for durable use.

The built-in elements, if required, can be covered by separate certificates e.g. pushbuttons, signal lamps, measuring instruments and/or terminals, or other separate approved components of increased safety "e" and flameproof enclosure "d" and encapsulation "m".

Enclosures with one, two or three units can exclusively be used for the installation of the terminal blocks with the type of protection increased safety "e", covered by separate certificate.

The identification with the symbols of the types of protection is adapted to the components that actually installed.

#### 2. Type assortment

GHG 44. .... R.... Legend of the signs from left to right

1, 2, 3	Code for Manufacturer		
4, 5	Code for control unit version		
6	Code for enclosure size $\begin{array}{cccccccccccccccccccccccccccccccccccc$		
	444 = 134		
	443 = 260 × 160 × 91 (light alloy) 443 = 230 × 280 × 111 (light alloy)		
7, 8	Enclosure material Moulded plastic = 2 VA material = 3 Light alloy = 4		
9, 10, 11, 12, 13, 14, 15	No influence on Ex-protection		

#### ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY



3rd amendmento to IECEx BKI 07.0023

Page 2 of 2

#### 3. General parameters

#### Electrical data

Rated voltage max. 690 V
Rated current max. 40 A or 63 A
Rated cross-sectional max 6 mm<sup>2</sup>
Power consumption for signal lamps max 1,8 W / per lamps
for MCB/RCB max. 11,2 W / per MCB/RCB for T6
15,5 W / per MCB/RCB for T5
38,3 W / per MCB/RCB for T4

The electrical data for the built-in components can be gathered from the respective certificates Electrical safety I class of electrical safety standards (MSZ EN-IEC 60598)

#### 4. Ambient temperature

Subject to the sealing used, the maximum ambient temperature is -55  $^{\circ}\text{C} \leq$  Tamb  $\leq$  +55  $^{\circ}\text{C}$ 

#### 4.1 Ingress protection and working temperature range for control and display element

#### 4.1.1 Dust

The actuator elements used in the enclosure may also be employed in areas in which a potentially explosive atmosphere as a mixture of dust and air can occasionally form.

Control and display element ( actuator )	IP protection	Working temperature range
Signal lamp GHG 410 1413	IP66	-20 °C to +40 °C
Push button GHG 410 1402	IP66	-20 °C to +40 °C
Double pushbutton GHG 410 1407	IP66	-20 °C to +40 °C
Measuring instrument AM72 GHG 410 1917	IP66	-20 °C to +40 °C
Mushroom-head emergency button GHG 410 1405	IP66	-20 °C to +40 °C
Control switch Ex 29/28 GHG 420 / 430 10	IP66	-20 °C to +40 °C
Control switch Ex 23 GHG 420 / 430 10	IP66	-20 °C to +40 °C
Dummy element GHG 410 6666	IP66	-55 °C to +90 °C
Measuring instrument AM 45 GHG 410 1915	IP66	-20 °C to +60 °C
Mushroom-head emergency button with lock GHG 410 1406	IP6X	-20 °C to +55 °C
Key operated pushbutton GHG 410 1404/35	IP6X	-20 °C to +55 °C
Rotary switch Ex 41 GHG 410 14 08/	IP6X	-20 °C to +55 °C
Potentiometer GHG 410 1427	IP6X	-20 °C to +55 °C

#### 4.1.2 Gas

For gas applications the values of clause 4 are applicable with the following restrictions:

- provision of an M45 measuring instrument actuator
  - In that case the minimum ambient temperature range is reduced to -40°C.
- installation of a control switch type Ex 23 GHG23, ....R...., including the actuator type 8602/.
   In that case the minimum ambient temperature range is reduced to -20°C.

#### 5. Ingress protection: IP66 to IEC 60529 (moulded plastic enclosure)

#### Notes for manufacturing and operation

The "Notes for manufacturing and operation" will also apply to the supplement.

The enclosure made from material SMC 190 has to carry the following warning: "Clean with moist cloth only."

## IEC TECEX

#### ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY

**IECEX BKI 07.0023** 

Page 1 of 3

#### 1. Description

Control units of type GHG 44. ....V.... consist of a bottom part and a cover with separately approved internal sealing device. They are made of moulded plastic or VA4 sheet steel or light alloy.

Rail-type webs or top-hat rails have been grooved (plastic enclosure) or riveted (metal enclosure) into the bottom part of the enclosure. They are intended for take up the built-in elements.

Assembling of the control units is permitted.

Attached Ex cable entries has to be covered by separate certificate.

Both variants are suitable for durable use.

The built-in elements, if required, can be covered by separate certificates e.g. pushbuttons, signal lamps, measuring instruments and/or terminals, or other separate approved components of increased safety "e" and flameproof enclosure "d" and encapsulation "m".

Enclosures with one, two or three units can exclusively be used for the installation of the terminal blocks with the type of protection increased safety "e", covered by separate certificate.

The identification with the symbols of the types of protection is adapted to the components that actually installed.

#### 2. Type assortment

GHG 44. .... R.... Legend of the signs from left to right

1, 2, 3	Code for Manufacturer
4, 5	Code for control unit version
6	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
	444 =       134       × 271       × 135 (moulded plastic)         447 =       271       × 817       × 135 (moulded plastic)         448 =       271       × 271       × 135 (moulded plastic)         448 =       271       × 271       × 210 (moulded plastic)         449 =       271       × 544       × 135 (moulded plastic)         449 =       271       × 544       × 210 (moulded plastic)
	443 = 260 × 160 × 91 (light alloy) 443 = 230 × 280 × 111 (light alloy)
7, 8	Enclosure material Moulded plastic = 2 VA material = 3 Light alloy = 4
9, 10, 11, 12, 13, 14, 15	No influence on Ex-protection

#### ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY



**IECEX BKI 07.0023** 

Page 2 of 3

#### 3. General parameters

#### Electrical data

Rated voltage max. 690 V
Rated current max. 40 A or 63 A
Rated cross-sectional max 6 mm<sup>2</sup>
Power consumption for signal lamps max 1,8 W / per lamps
for MCB/RCB max. 11,2 W / per MCB/RCB for T6
15,5 W / per MCB/RCB for T5
38,3 W / per MCB/RCB for T4

The electrical data for the built-in components can be gathered from the respective certificates Electrical safety I class of electrical safety standards (MSZ EN-IEC 60598)

#### 4. Ambient temperature

Subject to the sealing used, the maximum ambient temperature is -55  $^{\circ}\text{C} \leq$  Tamb  $\leq$  +55  $^{\circ}\text{C}$ 

4.1 Ingress protection and working temperature range for control and display element

Control and display element ( actuator )	IP protection	Working temperature range
Signal lamp GHG 410 1413	IP66	-20 °C ≤ Tamb ≤ +40 °C
Signal lamp GHG 410 1402	IP66	-20 °C ≤ Tamb ≤ +40 °C
Double pushbutton GHG 410 1407	IP66	-20 °C ≤ Tamb ≤ +40 °C
Measuring instrument AM72 GHG 410 1917	IP66	-20 °C ≤ Tamb ≤ +40 °C
Mushroom-head emergency button GHG 410 1405	IP66	-20 °C ≤ Tamb ≤ +40 °C
Control switch Ex 29/28 GHG 420 / 430 10	IP66	-20 °C ≤ Tamb ≤ +40 °C
Control switch Ex 22 GHG 420 / 430 10	IP66	-20 °C ≤ Tamb ≤ +40 °C
Dummy element GHG 410 6666	IP66	-55 °C ≤ Tamb ≤ +90 °C
Measuring instrument AM 45 GHG 410 1915	IP66	-20 °C ≤ Tamb ≤ +60 °C
Mushroom-head emergency button with lock GHG 410 1406	IP6X	-20 °C ≤ Tamb ≤ +55 °C
Key operated pushbutton GHG 410 1404/35	IP6X	-20 °C ≤ Tamb ≤ +55 °C
Rotary switch Ex 41 GHG 410 14 08/	IP6X	-20 °C ≤ Tamb ≤ +55 °C
Potentiometer GHG 410 1427	IP6X	-20 °C ≤ Tamb ≤ +55 °C

5. Ingress protection: IP66 to IEC 60529 (moulded plastic enclosure)

#### Notes for manufacturing and operation

The "Notes for manufacturing and operation" will also apply to the supplement.

The enclosure made from material SMC 190 has to carry the following warning: "Clean with moist cloth only."

#### ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY

**IECEx BKI 07.0023** 

Page 3 of 3

Data sheet SMC 190

Data sheet for plastic materials used

	Drawings		
	Description No. 4186 (20 sheets)		1999. 10. 10.
	List of component variant and their combinations (1 shee	t)	1999. 12. 10.
	Drawing No GHG 41-2-4045	.,	1999. 09. 27.
	GHG 73-4-3739		1999. 09. 27.
	GHG 44-3-4051		1999. 09. 27.
	GHG 44-3-4050		1999. 09. 27.
	GHG 44-3-4049		1999. 09. 27.
	GHG 44-3-4048		1999. 09. 27.
	Test report No. PTB Ex 99-19131 (5 sheets)		1999. 12. 16.
	Description No. 4186 Supplement	(1 sheet)	2002. 03. 15.
	Test protocols and information documents:	(1 0.1001)	2002. 00. 10.
	Test protocol of DMT No. BVS PP 02.2017EG		2002. 02. 28.
	No. BVS PP 02.2018EG		2002. 02. 28.
	Test report No. PTB Ex 02-12099 (2 sheets)		2002. 05. 13.
	Description	6 sheet	2006. 09. 06
	Drawing No. GHG 670-4-4504	1 sheet	2006. 07. 27
	Drawing No. GHG 610 1190 R0001	1 sheet	2006. 07. 27
	Drawing No. GHG 610 1191 R0001	1 sheet	2006. 07. 27
	Drawing No. GHG 410-3-4476	1 sheet	2006. 07. 27
	Parts No. GHG 410-3-4476	1 sheet	2006. 07. 27
	Drawing No. GHG 410-3-4475	1 sheet	2006. 07. 27
	Parts No. GHG 410-3-4475	1 sheet	2006. 07. 27
	Drawing No. GHG 410-3-4479	1 sheet	2006. 07. 27
	Parts No. GHG 410-3-4479	1 sheet	2006. 07. 27
	Drawing No. GHG 410-3-4542	1 sheet	2006. 07. 27
	Parts No. GHG 410-3-4542	1 sheet	2006. 07. 27
	Test Report PTB Ex 06-16295	4 sheet	2006. 11. 16
Test Records of Cooper Crouse-Hinds No. 01-MI4-B1-07042006			
Test Records of Cooper Crouse-Hinds No. 02-MI4-B1-28092005			
	Test Records of PTB dd. 29-08-1997		
	Test Records of Cooper Crouse-Hinds No. 02-MI4-B1-23092004		
	Test Records of Cooper Crouse-Hinds No. 01-MI4-B1-03022005		
	Test Records of Cooper Crouse-Hinds No. 01-MI4-B1-18	112004	
	Data sheet for elastomers		
	D-4b4 CMC 400		