

## **Hydraulic Crimping Tool**



## HCT-S1

HCT-S1 Hydraulic Crimping Tool with interchangeable die is suitable for compression of electrical connector on copper or aluminum lug and C-Clamp with 180 degree fully rotated tool head.



Specification Crimping force 60 KN Stroke 17 mm Length 460 mm Weight 3.3 kg



Application
Copper Lugs size 10-300 mm<sup>2</sup>
C-Clamp Code no. CCC 10-10 to CCC 70-70



## HCT-M1

HCT-M1 Hydraulic Crimping Tool with interchangeable die is suitable for compression of electrical connector on copper or aluminum lug and C-Clamp with 180 degree fully rotated tool head. The double speed action provides a fast advance speed for rapid approach of the dies to the connector and a lower more powerful speed for crimping.



Specification Crimping force 120 KN Stroke 42 mm Length 550 mm Weight 7.0 kg



Application Copper Lugs size 10-400 mm<sup>2</sup> C-Clamp Code no. CCC 10-10 to CCC 185-95



## HCT-P1

HCT-P1 Hydraulic Pump Set is suitable for electrical connector and a die for connector copper or aluminium lug and C-Clamp in advance operation and no electricity. Oil can be releasedquickly with 2 stages of high and low pressure which are available besides quick coupling.



Specification Crimping force 540 KN Stroke 28 mm Length 380 mm Weight 43.4 kg Hydraulic pump 11.4 kg Crimping tool 32 kg



Application Copper Lugs size 400-1000 mm<sup>2</sup> C-Clamp Code no. CCC 95-35 to CCC 300-300