


## Universal Connector




Universal Connector is made of Stainless Steel. There are two types of connecting process cross joint and parallel joint. The contact resistance shall be less than 1 mΩ, as well as the connected conductors tensile force shall be more than 900 N

Code No.	Cable Size (mm)	Torque (N·m)	Bolt Size (mm)	Weight (kg)
LCAC-SS-10-M10	8-10	26	M10 (1.50x35)	0.11



## Shear Bolt Connector




Shear Bolt Connector provide connection for cross joint or parallel joint. Easy installation, no torque wrench required.

Code No.	Cable Size (mm)	Torque (N·m)	Bolt Size (mm)	Weight (kg)
LCAC-SS-10-M10-N	8-10	26	M10 (1.50x35)	0.11



## Rebar Clamp Connector with Shear Bolt



The universal clamp connector for connection type T-joint, cross joint and parallel joint between rebar to rebar, rebar to round conductor, round conductor to round conductor. The shear bolt provide quick installation and the superior of connection.

Code No.	Rebar Size (mm)	Conductor Size (mm)
GCRER-SB-25-10	16 - 25	8 - 10
GCRER-SB-25-20	16 - 25	14 - 20
GCRER-SB-40-10	32 - 40	8 - 10
GCRER-SB-40-20	32 - 40	14 - 20

