

1. PRODUCT NAME AND IDENTIFICATION

Product Name:	JCP 705 FAST LUBE
Chemical Name & Synonyms:	N/A
CAS Number:	N/A, Mixture
Company Name:	JCP GROUP(THAILAND) CO., LTD.
Tel & Fax.: +(66)34-412-824	Emergency: +(66)85-105-6034

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS#	% by Wt.	OSHA TWA	ACGIH-TWA
			(ppm)	(ppm)
ALIPHATIC HYDROCARBON	64742-9-0	70 - 80 %	N/A	N/A
MIXTURE				
ETHYL ACETATE	141-78-6	20 - 30 %	N/A	N/A
SODIUM SULFONATE	68608-26-4	5 - 20 %	N/A	N/A
PROPELANT	74-98-6	20 - 30 %	N/A	N/A

3. HAZARDS IDENTIFICATION

Emergency overview: Can cause irritation or damage to eyes and skin. Harmful if swallowed.

Routes of Exposure: Inhalation: [1] Ingestion: [1]

Eyes: Causes eye irritation.

Skin: May cause skin irritation.

Inhalation: Prolonged skin contact may defat the skin and produce dermatitis. Harmful if inhaled and may cause delayed lung injury.

Absorption: [✓]

Ingestion: Ingestion may cause irritation to mucous membranes. Causes headache, drowsiness or other effects to the central nervous system. Aspiration hazard if swallowed - can enter lungs and cause damage.

Carcinogenicity: Contains no listed carcinogens.

4. FIRST AID MEASURES

General Advice: Avoid contact with skin, eyes and clothing. Show this safety data sheet to the doctor in attendance. **Eye Contact**: Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.

Skin Contact: Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion: Drink 1 or 2 glasses of water. Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Notes to Physician: Aspiration hazard if swallowed - can enter lungs and cause damage.

5. FIRE FIGHTING MEASURES



Flash Point > 81°F / > 27°C Method Seta Closed Cup Autoignition Temperature N/A Upper 11.5 Lower 0.5 Suitable Extinguishing Media Water spray. Foam. Dry chemical. Carbon dioxide (CO2). Specific Hazards Arising from the Chemical Solvent vapors are heavier than air and may spread along floors .

Vapors may ignite and explode. Material can create slippery conditions. Keep product and empty

container away from heat and sources of ignition. Risk of ignition.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA	Health 2	Flammability 4	Instability 0
HMIS	Health 2	Flammability 4	Instability 0

6. ACCIDENTAL RELEASE (SPILL MEASURES)

Personal Precautions	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13)
Methods for Cleaning Up	Pick up and transfer to properly labelled containers. Never return spills in original containers for re-use.
Neutralizing Agent	Not applicable

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with			
	skin, eyes an	d clothing. Avoid	breathing vapor	s, mist or gas.
Storage	Keep contain	er tightly closed	in a dry and well	-ventilated place. Keep away from heat
	and sources of	of ignition. Keep	in properly labell	ed containers.
Storage Temperature	Minimum 35	°F / 2°C	Maximum 12	20°F / 49°C
Storage Conditions	Indoor X	Outdoor	Heated	Refrigerated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
ALIPHATIC HYDROCARBON MIXTURE	No data available	No data available	No data available
ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm TWA: 1440 mg/m3	TWA: 400 ppm
PROPELANT	TWA : 1000 ppm	TWA : 1000 ppm TWA : 1800 mg/m ³	IDLH : 2100 ppm TWA : 1000 ppm TWA : 1800 mg/m ³

Engineering Measures Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

Personal Protective EquipmentEye/Face ProtectionSafety glasses with side-shields.



location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES (Typical)

Physical State	Liquid	Viscosity	Non viscous
Color	Colorless	Odor	Characteristic Odor
Appearance	Transparent-Hazy	рН	Not applicable
Specific Gravity	0.84	Bulk Density	Not applicable
Evaporation Rate	24.77 (Butyl acetate=1)	Percent Volati	le (Volume) 75.4
VOC Content (%)	41.901	Vapor Pressu	r e 1547 mmHg @ 70 ∘F
Vapor Density	1.70	Solubility	Insoluble
Boiling Point/Range	71 °C		

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Heat, flames, and sparks.
Incompatible Products	Strong oxidizing agents.
Hazardous Decomposition Products	Carbon oxides.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

ALIPHATIC HYDROC	ARBON MIXTURE
LD50 Oral Rat	>5000 mg/kg
LC50 Inhalation Rat	>20 mg/l 4h

ETHYL ACETATE

LD50 Oral Rat5620 mg/kgLD50 Dermal Rabbit>18000 mg/kg

PROPELANT LC50 Inhalation Rat 658 mg/l 4h

 Chronic Toxicity
 Mutagenicity
 The possibility of an embryotoxic effect has not yet been fully assessed.

 Sensitization
 no data available

 Developmental Toxicity
 no data available

 Reproductive Toxicity
 no data available

 Target Organ Effects
 CNS

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.ACGIHnot applicable



IARC	not applicable
NTP	not applicable
OSHA	not applicable
Other	not applicable

12. ECOLOGICAL INFORMATION

Component Information Toxicity to Algae	Mix chlorinated compound EC0 = 125 mg/l Sc. Quadricauda		
Toxicity to Fish	LC50= 220 mg/L Lepomis macrochirus		
	LC50=45 mg/L Pimephales promelas		
Microtox	EC0 = 500 mg/l Ps. pudita		
Water Flea	no data available		
log Pow	no data available		
Persistence and Degradability No information available Bioaccumulation: No information available			

Mobility: No information available Biodegradability: Result: Not readily biodegradable. Further information on ecology Biochemical Oxygen Demand (BOD): No data available.

13. DISPOSAL CONSIDERATIONS

Product DisposalDispose of as hazardous waste in compliance with local and national regulationsContainer DisposalEmpty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

Transport over land ADR/RID and GGVS/GGVE							
GGVS/GGVE Class	6.1	Number and Le	etter	15c			
ADR/RID Class	6.1	Number and Le	etter	15c			
Name of material:	1593 DICHLOF	ROMETHANE					
River transport AND/AD Not examine	NR						
Sea transport IMDG							
IMDG Class	6.1	UN-No.	1593		Package group		
EMS	6.1 - 02	MFAG	340				
Correct technical name	DICHLOROME	THANE					
Air transport ICAO-TI ar	nd IATA-DGR						
ICAO/IATA class	6.1	UN/IO-No.	1593		Package group	III	
Correct technical name	DICHLOROME	THANE					

The transport regulations are cited according to international regulations and in the form applicable in Germany (GGV/GGVE). Possible national deviations in other countries are not considered.



15. REGULATORY INFORMATION

Labelling according to EC Directives

Symbol:	Xn	Harmful immediately and show this container or label
R-phases	R 40	Possible risk of irreversible effects
S-phass	$S\ 23.2\ -\ 24/25\ -\ 36/37$	Do not breath vapor. Avoid contact with skin and eyes. Wear suitable
		Protective.
EC -No.	200-838-9	EC Label

16. OTHER INFORMATION

The above information is based on data available to us and is believed to be correct. However, no warranty, merchantability, fitness for any use or any other warranty is expressed or to be implied regarding the accuracy of these data, the result to be obtained from the use thereof, the hazards connected with the use of the material, or that any such use will not infringe any patent. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility resulting from its use. This information is furnished upon the condition that the person receiving it shall make his own determination for the suitability of the material for his particular purposes.