

NBR Rubber Gasket Style 9210



Montero NBR Rubber Gasket Style 9210 is premium grade nitrile, 60 to 85 duro, generally resistance to most hydrocarbon, fats, oils, greases, hydraulic fluids, chemicals and solvents,

Technical Data Sheet

Type	: Nitrile
Color	: Black
Temperature Range (°C)	: - 29 °C to + 121 °C
Max. Pressure (bar)	: 25 bar
P x T max. (bar x °C)	: 1000 bar x °C
Compression Set, ASTM Method B (%)	: 20 %
Elongation, min., (%)	: 500 %
Tensile Strength, min.,	: 14 N/mm²
ASTM D412, (N/mm²)	
Hardness (Shore A)	: 60 to 85 ± 5 Shore A
Thickness available	: 0.5, 0.8, 1, 1.5, 2, 3, 5, 6, 8, 10 mm.

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Montero. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice. Montero is a registered trademark for packing, seals, gaskets, and other products of Montero.