

MG-787

MONTERO PACKING FOR VALVES

■ COMPOSITION

Packing manufactured by FIBRAS Y ELASTOMEROS S.A. from high quality pure expanded mineral graphite yarns with inhibitor corrosion.

In order to obtain a greater pressure resistance to use it in valves, each strand is reinforced with a wire mesh covering, and braided by the diagonal system, which confers to the packing some excellent mechanical properties and reducing the possibility of braid extrusions.

This packing can work in the highest pressures and temperatures and can be used in all type of valves.

This product can be supplied in performed rings without use the anti extrusion rings as MG 787 avoid the extrusion itself.

It is recommended where it is necessary a control of emissions.

■ PARAMETER

MG-787	Maximum working conditions
TEMPERATURE (°C)	-200+650
PRESSURE (Bar)	350
VELOCITY (m/s)	-
P-H	0-14

■ APLICACIONES

For valves and sealing applications with high temperatures and pressures.

Other applications:
Exhausts, turbine, mills, etc.

Valves & equipment in:

POWER & NUCLEAR PLANT
PAPER & PULP MILL.
CHEMICAL & PETROCHEMICAL INDUSTRY.
SUGAR & FOOD INDUSTRY.
DESALATION PLANT
WASTEWATER TREATMENT
STEEL FACTORIES & FOUNDRIES
SHIPYARDS
MINERY
PROCESS INDUSTRIES.



Montero®

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11
48510 Valle de Trapaga, Vizcaya, España.
Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83
e-mail: access@monterofye.com
http://www.monterofye.com

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

