

MS-315

ARAMID GLAND PACKING WITH HIGH ABRASION RESISTANCE

■ COMPOSITION

Packing manufactured by MONTERO from continuous aramid filament, which are impregnated with PTFE and other lubricants.

This packing has a high mechanical resistance therefore it is necessary to follow carefully the installation procedures in order to not to damage the pump shaft.

Perfectly adjustable to every kind of groove in centrifugal and alternative pumps and every rotary equipment.

Packing used in whole services but in special for sugar and paper factories and for high abrasive and viscous fluids where mechanical resistance of the continuous aramid prevent from detrition.

Follow carefully MONTERO's installation procedures.

■ PARAMETER

MS-315	Maximas condiciones
TEMPERATURE (°C)	270
PRESSURE (Bar)	250
VELOCITY (m/s)	15
P-H	2-12

■ APLICACIONES

Reciprocation and piston pumps

Other applications:
Pressure and dynamic equipment, turbines, compressors and, on the whole, every centrifugal movement at high pressures.

Pumps & equipment in:

POWER & NUCLEAR PLANT
PAPER & PULP MILL.
CHEMICAL & PETROCHEMICAL INDUSTRY.
SUGAR & FOOD INDUSTRY.
CEMENT PLANT.
STEEL & FOUNDRY FACTORIES.
MARINE INDUSTRY, etc.



Montero[®]

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11
48510 Valle de Trapaga, Vizcaya, España.
Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83
e-mail: access@monterofye.com
<http://www.monterofye.com>

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

abcde