

swimming pool. The component design is easy to assemble, and the installation is simple to operate; A variety of connection sizes can meet different usage scenarios. The RDG300K is equipped with strainer basket, while the RDG300X is not, so you will have more choices.

Features:

- Simple installation and easy operation
- The sand filter and the water pump are precisely matched, so that the performance of the unit is optimal and efficient
- The combined base can meet the requirements of different scenarios
- Unitized thermal plastic filter tank, tough, durable and suitable for many different weather conditions.
- Pump built-in heat protector makes the service life longer
- The pump meets F insulation class and IPX5 protection requirement
- The pump has good sealing and anti-corrosion performance, and runs extremely quiet
- A variety of connection sizes, suitable for 32138mm flexible hose,
 1.5"/50mm pipe
- The whole unit includes hoses and other necessary accessories



RDG300X





RDG300K SERIES SAND FILTER SYSTEM

Includes:

- 12"Durable top mount plastic filter tank
- Standard: 4-Way Multiport Valve (Optional: 6-Way Multiport Valve)
- 0.33HP Water Pump

(With Strainer Basket)










RDG300X SERIES SAND FILTER SYSTEM Includes:

- 12"Durable top mount plastic filter tank
- Standard: 4-Way Multiport Valve (Optional: 6-Way Multiport Valve)
- 0.25HP Water Pump (Without Strainer Basket)





QH. Curve of the pump



Product Dimensions

Model	RDG300K	RDG300X	
A(mm)	183	140	
B(mm)	297	340	
C(mm)	525	525	
D(mm)	305	305	
H(mm)	546	546	



6-way multiport valve



Technical parameters

Model	Filter size	Pump Power (HP)	Filter Area (m²)	Flow rate		Pump flow rate		Sand weight	Multiport	Pipe
				m³/h	lpm	m³/h	lpm	0.5-0.8mm (kg)	valve	connection
RDG300K	12"	0.33	0.073	3.65	60.8	6.5	108.33	20	4-way	32/38mmflexible hose 1.5"/50mm pipe
RDG300X	12"	0.25	0.073	3.65	60.8	8.2	136.67	20	4-way	