

SWPB SERIES PUMP

SWPB series pump is designed for the market that likes to use American pump.



WPB series pumps are designed for the market who likes to use American pump with high flow and high lift. The overall size is reference to the market habit.

Features:

- Inlet and outlet be reinforced by a stainless steel ring.
- Integral structure handle, convenient installation.
- Thermal protector: single phase.
- Insulation: F.
- Protection: IP55
- Max suction: 3 m.
- Liquid temperature: 5-50 °C.
- Ambient temperature: up to 50 °C.
- Single phase: 220V/50Hz.
- 220V/60Hz, 380V/50Hz are available on request.

Model	Q-max (m ³ /h)	H-max (m)	Horsepower (HP)	Rated Power (KW)	Phase	Voltage (V)	(Amps)	Connection size	L Length (mm)	H Height (mm)
WL-SWPB075	17.1	12	0.75	0.55	1	220	3.2	60.3mm or 63mm	572	243
WL-SWPB100	18.9	15	1.0	0.75	1	220	3.8	60.3mm or 63mm	572	243
WL-SWPB120	20.1	17	1.2	0.9	1	220	4.6	60.3mm or 63mm	572	243
WL-SWPB150	24	19	1.5	1.1	1	220	5.4	60.3mm or 63mm	572	243
WL-SWPB200	28.8	21	2.0	1.5	1	220	7.0	60.3mm or 63mm	572	243
WL-SWPB250	31.8	21	2.5	1.85	1	220	8.6	60.3mm or 63mm	572	248
WL-SWPB300	33	22	3.0	2.2	1	220	10	60.3mm or 63mm	585	258

Product performance curve

