# SAFETY DATA SHEET

(GHS, Appendix 4)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Canthoxal EC N° : 226-749-5 CAS N° : 5462-06-6

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Industrial-grade aromatic raw material, not intended for retail sale

### 1.3. Details of the supplier of the safety data sheet

Registered company name : Aromatics Original Material Co., Ltd. Address : 3/8 1st floor Bangwaek Rd, Bangpai, Bangkae, Bangkok 10160 Thailand.

## **SECTION 2 : HAZARDS IDENTIFICATION**

2.1. Classification of the substance or mixture

#### GHS compliant.

Acute oral toxicity, Category 5 (Acute Tox. 5, H303).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Acute hazard, Category 2 (Aquatic Acute 2, H401).

This substance does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

## 2.2. Label elements

## GHS compliant.

Hazard pictograms :



GHS07Signal Word :WARNINGProduct identifiers (list of classified components) :CAS 5462-06-64-METHOXY-ALPHA-METHYLBENZENEPROPANALHazard statements :H303May be harmful if swallowed.H317May cause an allergic skin reaction.H401Toxic to aquatic life.

Precautionary statements - Prevention :

	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
	Precautionary statements - Res	ponse :
	P302 + P352	IF ON SKIN: Wash with plenty of water/
	P312	Call a POISON CENTER/doctor/ if you feel unwell.
	P362 + P364	Take off contaminated clothing and wash it before reuse.
,	2 Other herends	

#### 2.3. Other hazards

No data available.

#### **SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1. Substances

## **Composition :**

Identification	GHS	Note	%
CAS: 5462-06-6 EC: 226-749-5 REACH: 02-2119848330-44-0000 4-METHOXY-ALPHA-	GHS07 Wng Acute Tox. 5, H303 Skin Sens. 1B, H317		100%
METHYLBENZENEPROPANAL CAS: 128-37-0 EC: 204-881-4 REACH: 01-2119565113-46-0000 BUTYLATED HYDROXYTOLUENE	Aquatic Acute 2, H401 GHS09 Wng Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[1]	0 <= x % < 1

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

## **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

#### 5.1. Extinguishing media

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

## 5.3. Advice for firefighters

No data available.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

## 6.3. Methods and material for containment and cleaning up

#### Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the substance is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this substance.

## 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention :

Handle in well-ventilated areas. Prevent access by unauthorised personnel.

# **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the substance is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

## Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### Packaging

Always keep in packaging made of an identical material to the original.

## 7.3. Specific end use(s)

No data available.

# **SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1. Control parameters

## **Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

			20	·	,
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	2 (IFV) mg/m3			A4	
- South Africa / DME (De	partment of Mine	erals and Energy,	2006) :		
- South Africa / DOL RL	(Department of L	abour, Recomme	ended limits, 199	5):	
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	10 mg/m3				
- Germany - AGW (BAuA	A - TRGS 900, 08	3/08/2019) :			
CAS	VME :	VME :	Excess	Notes	
128-37-0		10 mg/m <sup>3</sup>		4 (II)	
- Australia (NOHSC: 3008	8, 1995) :				
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	10 mg/m3			Н	
- Belgium (Arrêté du 09/0	3/2014, 2014) :				
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	2 mg/m <sup>3</sup>				
- Canada / Alberta (Occup	ational health an	d safety code, 20	09) :		
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	10 mg/m3				
- Canada / British Colomb	ia (2009) :				
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :

- Canada / Ontario (Contrai of exposure to biological or chemical agents, regulation 491/2009) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37.010 mg/m3NA2 Canada / Quebec (Regulations on occupational health and safety) :NA128-37.010 mg/m32 Canada / Quebec (Negulations on occupational health and safety) :2 Canada / Quebec (Negulations on occupational health and safety) : </th <th>128-37-0</th> <th>2 (V) mg/m3</th> <th></th> <th></th> <th></th> <th></th> <th></th>	128-37-0	2 (V) mg/m3					
128-37-02 mg/m3IVA- Canada / Quebec (Regulations on occupational health and safety) : Denmark (2008) :StofTWAVSTELLoftvaerdiAnm128-37-010 mg/m3- France (INRS - ED984 / 2019-1487) :CASVME-pm:VME-mg/m3 :VLE-mg/m3 :Notes :TMP No :128-37-0-10 Finland (HTP-värden 2016) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m30 mg/m3 Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2017) :CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m3 Greece (90/1999) :-10 mg/m3CASTWA :STEL :Ceiling ::Definition :Criteria :-128-37-010 mg/m3 Rulaysia :STEL :Ceiling ::Definition :Criteria :-128-37-010 mg/m3 New Zealand (Workplace Exposure standards, 2002) : Rulaysia :STEL :Ceiling ::Definition :Criteria :-128-37-010 mg/m3 New Zealand (Workplace Exposure standards	- Canada / Ontario (Con	trol of exposure	to biological or ch	emical agents, re	gulation 491/200	)9):	
- Canada / Quebec (Reyulations on occupational health and safety) ::       -         - Demark (2008) :       TWA       VSTEL       Loftwaerdi       Anm         128-37-0       10 mg/m²         - France (INRS - ED984 / 2019-1487) :       VME-mg/m3 : VLE-ppm:       VLE-mg/m3 : Notes :       TMP No :         128-37-0       -       0       -       -       -         - Finland (ITTP-varden 2016) :        Ceiling :       Definition :       Criteria :         - Spain (Instituto Nacional & Sequridad e Higene en el Talajo (INSHT), 2017) :       CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         - Spain (Instituto Nacional & Sequridad e Higene en el Talajo (INSHT), 2017) :       CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         - Spain (Instituto Nacional & Seguridad e Higene en el Talajo (INSHT), 2017) :       CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         - Spain (Instituto Nacional & Seguridad e Higene en el Talajo (INSHT), 2017) :       CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         - Spain (Instituto Nacional & Seguridad e Higene en el Talajo (INSHT), 2017) :       CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :	CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
- Denmark (2008):TWAVSTELLoftwardiAnm128-37-010 mg/m³- France (INRS - ED984 / 2019-1487):CASVME-ppm:VLE-ppm:VLE-ppm:VLE-mg/m3:Notes:TMP No :128-37-0-10 Finland (HTP-värden 2016):CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m320 mg/m3 Spain (Instituto Nacional de Seguridad + Higiene en el Trabajo (INSHT), 2017):CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m3-0 mg/m3 Greece (90/1999):-Criteria:10 mg/m3 Ireland (Code of practice for the Chemical Agents Regulations, 2016):Criteria: Sa7-010 mg/m3 Alaysia:TWA:STEL:Ceiling:Definition:Criteria: Adaysia:TWA:STEL:Ceiling:Definition:Criteria: <td< td=""><td>128-37-0</td><td>2 mg/m3</td><td>-</td><td>-</td><td>-</td><td>IVA</td><td></td></td<>	128-37-0	2 mg/m3	-	-	-	IVA	
StofTWAVSTELLoftwardAnm128-37-010 mg/m³ <t< td=""><td>- Canada / Quebec (Reg</td><td>ulations on occup</td><td>pational health and</td><td>l safety) :</td><td></td><td></td><td></td></t<>	- Canada / Quebec (Reg	ulations on occup	pational health and	l safety) :			
128-37-010 mg/m³- France (INRS - ED984 / 2019-1487) :VME-mg/m3 : VLE-ppm:VLE-mg/m3 : Notes:TMP No :128-37-0-10 Finland (HTP-vidred=VI):VLE-mg/m3 : Notes:TMP No :128-37-010 mg/m320 mg/m3 Spain (Instituto Nacional de Seguridad e Higene en el Trabajo (INSHT).Definition :Criteria :-128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :128-37-010 mg/m310 mg/m3 Greece (90/1999) :-10 mg/m3128-37-010 mg/m310 mg/m3Criteria :128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Malaysi :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stander :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace :STEL :Ceiling :Definition :Criteria : <td>- Denmark (2008) :</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	- Denmark (2008) :						
CASVME-ppm:VME-mg/m3:VLE-ppm:VLE-mg/m3:Notes:TMP No:128-37-0IO128-37-0IO mg/m320 mg/m3-Definition:Criteria:128-37-0IO mg/m320 mg/m3 Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (NSHT), 2017) :CASTWA:STE :Ceiling:Definition:Criteria:128-37-0IO mg/m3-Ceiling:Definition:Criteria:128-37-0IO mg/m3-IO mg/m3 Ireland (Code of practice for the Chemical Agents Regulations, 2016) :Criteria:CASTWA:STE :Ceiling:Definition:Criteria:128-37-0IO mg/m3128-37-0IO mg/m3CASTWA:STE :Ceiling:Definition:Criteria:128-37-0IO mg/m320 mg/m3 Mexico:CASTWA :STE :Ceiling:Definition:Criteria:128-37-0IO mg/m320 mg/m3 Nexico:	Stof	TWA	VSTEL	Loftvaerdi	Anm		
CASVME-ppn:VME-ppn:VLE-ppn:VLE-pg/m3:Notes:TMP No:128-37-0-10 Finland (HTP-varden 2016):STEL:Ceiling:Definition:Criteria:-128-37-010 mg/m320 mg/m3 Spain (Instituto Nacional de Seguridad e Higtene en el Trabajo (INSHT), 2017):CASTWA:STEL:Ceiling:Definition:Criteria:-128-37-010 mg/m3 Greece (90/1999):Ceiling:Definition:Criteria:CASTWA:STEL:Ceiling:Definition:Criteria: <td>128-37-0</td> <td>10 mg/m<sup>3</sup></td> <td></td> <td></td> <td></td> <td></td> <td></td>	128-37-0	10 mg/m <sup>3</sup>					
128-37-0II<	- France (INRS - ED984	4 / 2019-1487) :					
- Finland (HTP-värden 2016):CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 Spain (Instituto Nacional Vee Seguridae Ver Biene en el Trabijo (INSHT) > U17) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3-Criteria :Criteria :Criteria :128-37-0Criteria :128-37-010 mg/m3-STEL :Ceiling :Definition :Criteria :128-37-010 mg/m310 mg/m3Criteria :Criteria :128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3Malaysia :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure standard		VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
CASTWA : 10 mg/m3STEL : 20 mg/m3Ceiling :: 20 mg/m3Definition :: Criteria : 128-37-0Criteria : 128-37-0CASTWA : 10 mg/m3STEL : Ceiling ::Definition : Definition :Criteria : Criteria : 128-37-0CASTWA : 10 mg/m3STEL : 10 mg/m3Definition :: Criteria : Definition :Criteria : Criteria : Criteria : 128-37-0CASTWA : 10 mg/m3STEL : 0 mg/m3Definition : Criteria : Criteria : Definition :Criteria : Criteria : Criteria : Definition :CASTWA : 10 mg/m3STEL : Ceiling : Definition : Criteria : Definition : Criteria : Criteria : Criteria : 128-37-0Oriteria : Criteria : Criteria : Definition : Criteria : Criteria : Criteria : 128-37-0Criteria : Criteria : Criteria : Definition : Criteria : Criteria : Criteria : 128-37-0CASTWA : NA : STEL : CASSTEL : Ceiling : Definition : Criteria : Criteria : Criteria : Definition : Criteria : Criteria : Criteria : Definition : Criteria : Criteria : Criteria : Definition : Criteria : Criteria : Criteria : Definition : Criteria : Criteria : Di mg/m3CASTWA : NA : STEL : Ceiling : Definition : Criteria : Definition : Criteria : Definition : Criteria : Definition : Criteria : Di mg/m3CASTWA : NA : STEL : CASSTEL : Ceiling : Definition : Criteria : Criteria : Di mg/m3CASTWA : NA : NA : Di mg/m3STEL : Ceiling : <td>128-37-0</td> <td>-</td> <td>10</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td>	128-37-0	-	10	-	-	-	-
128-37-010 mg/m320 mg/m3- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2017) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3-Ceiling :Definition :Criteria :128-37-0Io mg/m3- Greece (90/1999) :-TWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3-Io mg/m3-Criteria :128-37-010 mg/m3Criteria :128-37-0- Ralaysia :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Malaysia :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Matysia :TWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure standards, 2002) :CASCriteria :128-37-0CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 New Zealand (Workplace Exposure functions, 2010 !IO mg/m3 </td <td>- Finland (HTP-värden 2</td> <td>2016) :</td> <td></td> <td></td> <td></td> <td></td> <td></td>	- Finland (HTP-värden 2	2016) :					
- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2017) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m³- Grecce (90/1999) :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m³ Ireland (Code of practice for the Chemical Agents Regulations, 2016) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m³ Malaysia :CASTWA :STEL :Ceiling :Definition :Criteria :.128-37-010 mg/m³ Makico :CASTWA :STEL :Ceiling :Definition :Criteria :.128-37-010 mg/m320 mg/m3 Netw Zealand (Workplace Exposure standards, 2002) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Netwerlands / MAC-waarde (10 december 2014) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3- <td>CAS</td> <td></td> <td>STEL :</td> <td>Ceiling :</td> <td>Definition :</td> <td>Criteria :</td> <td></td>	CAS		STEL :	Ceiling :	Definition :	Criteria :	
CASTWA: TWA: 128-37-0TEL: 10 mg/m³Ceiling: 		-					
128-37-010 mg/m³- Greece (90/1999) :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3- Ireland (Code of practice for the Chemical Agents Regulations, 2016) :Criteria :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3STEL :Ceiling :Definition :Criteria :STEL :STEL :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3<	- Spain (Instituto Nacion	•		abajo (INSHT), 2	2017) :		
- Greece (90/1999):.CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m3- Ireland (Code of practice for the Chemical Agents Regulations, 2016):Criteria:CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m3-Definition:Criteria:128-37-010 mg/m3 Malaysia:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m3 Mexico:CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure standerds, 2002):CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure standerds, 2002):CASTWA:STEL:Ceiling:Definition:Criteria:128-37-010 mg/m3 Storenia (Liradin List, 04/06/2015):STEL:Ceiling:Definition:Criteria:128-37-010 (1) mg/m3 Switzerland (SUVAPRACE UTT):UEVLEVLEVLEVLEVLEVLEVLE- SascVMEVLEVLEVLEVLEVLEVLE <t< td=""><td></td><td></td><td>STEL :</td><td>Ceiling :</td><td>Definition :</td><td>Criteria :</td><td></td></t<>			STEL :	Ceiling :	Definition :	Criteria :	
CAS 128-37-0TWA : I0 mg/m3STEL : I0 mg/m3Ceiling :: I ng/m3Definition :: Criteria : Criteria :- Ireland (Code of practice for the Chemical Agents Regulations, 2016) : CAS TWA : I28-37-0STEL : STEL : VERDefinition : Criteria : Criteria :- Malaysia : CAS TWA : I28-37-0IO mg/m3 I-Ceiling :: Ceiling ::Definition : Criteria : Criteria :- Mataysia : CAS TWA : I28-37-0IO mg/m3 I-Ceiling :: Ceiling ::Definition : Criteria : Criteria :- Mexico : CAS CAS New Zealand (Workplace Exposure statice, 2002) :STEL : Ceiling : Ceiling ::Definition : Criteria : Criteria :- New Zealand (Workplace CAS I28-37-0IO mg/m3 IC mg/m3Ceiling :: Ceiling : Definition :Criteria : Criteria : Ceiling : IC mg/m3- Netherlands / MAC-waad L28-37-0IO mg/m3 I-Ceiling :: Ceiling ::Definition : Criteria : Criteria : IC mg/m3- Netherlands / MAC-waad L28-37-0IO mg/m3 I-IC Ceiling ::Definition : Criteria : Ceiling : IC mg/m3Criteria : Ceiling : IC mg/m3- Slovenia (Uradni List U-U/C/2015) : CAS I28-37-0TWA : IC MAE IC MAESTEL : Ceiling : IC MationsCriteria : Criteria : IC Mations- Switzerland (SUZAPR-VET): I28-37-0VME IC MAEVLE Valeur plafond Valeur plafond NotationsNotations- Switzerland (SUZAPR-VET): I28-37-0IO in mg/m3VLE Valeur plafond Valeur plafond NotationsNotations	128-37-0	10 mg/m <sup>3</sup>					
10 mg/m3- Ireland (Code of practice for the Chemical Agents Regulations, 2016) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Malaysia :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Mexico :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Mexico :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stat-tex, 2002) :Criteria :128-37-0Criteria :128-37-0- Netherlands / MAC-waar-te (10 december 2014) :Criteria :128-37-0Criteria : Slovenia (Uradni List, 04/06/2015) :Criteria :128-37-0 Slovenia (Uradni List, 04/06/2015) :Criteria :128-37-0Criteria :128-37-0 Switzerland (SUZAPR UDT) :CHVLEValeur plafondNotations Switzerland (SUZAPR UDT) :ULEValeur plafondNotations SWitzerland (Workplace exposure limity, EH40/2005, 2011) :VAleur plafond	- Greece (90/1999) :						
- Ireland (Code of practice for the Chemical Agents Regulations, 2016) :Ceiling :Definition :Criteria :CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m3CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m3 Mexico :CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m320 mg/m3128-37-010 mg/m320 mg/m3New Zealand (Workplace Exposure stards, 2002) :Criteria :Criteria :128-37-010 mg/m320 mg/m3Netherlands / MAC-warder (10 december 2014) :Ceiling :Definition :Criteria :128-37-010 mg/m3Slovenia (Uradni List, U4/06/2015) :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, U4/06/2015) :Ceiling :Definition :Criteria :128-37-010 mg/m3 Switzerland (SUVAPR-VETT) :Ceiling :Definition :Criteria :128-37-010 i mg/m340 i mg/m3 Switzerland (SUVAPR-VETT) :STEL :SEC Suterland (SUVAPR-VETT) :VLEVALE <td></td> <td>TWA :</td> <td></td> <td>Ceiling :</td> <td>Definition :</td> <td>Criteria :</td> <td></td>		TWA :		Ceiling :	Definition :	Criteria :	
CASTWA : 10 mg/m3STEL : Ceiling : Definition :Definition : Criteria : Criteria :128-37-010 mg/m3128-37-010 mg/m3128-37-010 mg/m3 Mexico : CASTWA : TWA : STEL :Ceiling : Ceiling : Definition :Criteria : Criteria :128-37-010 mg/m320 mg/m3 Mexico : CASTWA : TWA : STEL :Ceiling : Ceiling : Definition :Criteria : Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure standers, 2002) : CASCeiling : TWA : STEL :Definition : Ceiling : Definition :Criteria : Criteria :128-37-010 mg/m3 Netherlands / MAC-wadet (10 december 2014) : CASCeiling : TWA : STEL :Definition : Ceiling :Criteria : Criteria :128-37-010 mg/m3 Slovenia (Uradni List, 04/06/2015) : CASTWA : TUC (1) mg/m3 Switzerland (SUVAPRO 2017) : CASVMEVLEValeur plafond NotationsCriteria : Ceiling : SSC- SWitzerland (Workplace exposure limits, EH40/2005, 2011) :-SSC			-				
128-37-010 mg/m³- Malaysia :CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m3 Mexico :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m320 mg/m3128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stards, 2002) :Criteria :CASTWA :STEL :Ceiling ::Definition :Criteria :128-37-010 mg/m3128-37-010 mg/m328-37-010 mg/m328-37-010 mg/m328-37-010 mg/m3 Slovenia (Uradni List $+ Uo(2015)$ :Criteria :Criteria :-128-37-0TWA :STEL :Ceiling ::Definition :Criteria :128-37-0 Switzerland (SUVAPRUC 2017) :CASVMEVLEValeur plafonNotations128-37-010 i mg/m³40 i mg/m³SSC Sutzerland (SUVAPRUC Exposure limits, EHU/2005, 2011) :SSC	- Ireland (Code of pract	ice for the Chemi	cal Agents Regula	tions, 2016) :			
- Malaysia :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3· New Zealand (Workplace Exposure stards, 2002) :Criteria :20 mg/m3CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3· Netherlands / MAC-wardet (10 december 2014) :Criteria :10 mg/m3CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3· Slovenia (Uradni List, $\sqrt{10}/(C^2O15)$ :STEL :Ceiling :Definition :Criteria :128-37-0· Switzerland (SUVAPRO <dut) :<="" td="">STEL :Ceiling :Definition :Criteria :128-37-0· Switzerland (SUVAPRO<dut) :<="" td="">STEL :Ceiling :Definition :Criteria :128-37-0· Switzerland (SUVAPRO<dut) :<="" td="">VLEValeur plafondNotationsSEC· List-37-010 i mg/m³40 i mg/m³SEC<td></td><td></td><td>STEL :</td><td>Ceiling :</td><td>Definition :</td><td>Criteria :</td><td></td></dut)></dut)></dut)>			STEL :	Ceiling :	Definition :	Criteria :	
CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3New Zealand (Workplace Exposure stards, 2002) :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3Netherlands / MAC-wactorSTEL :Ceiling :Definition :Criteria :128-37-010 mg/m3Netherlands / MAC-wactorSTEL :Ceiling :Definition :Criteria :128-37-010 mg/m3Slovenia (Uradni List, $U/O(2015)$ :Ceiling :Definition :Criteria :128-37-010 mg/m3Slovenia (Uradni List, $U/O(2015)$ :Io (1) mg/m3Ceiling :Definition :Criteria :128-37-0TWA :STEL :Ceiling :Definition :Criteria :128-37-010 (1) mg/m340 i mg/m3SECCASVMEVLEValeur plafonNotations-128-37-010 i mg/m340 i mg/m3SEC	128-37-0	10 mg/m <sup>3</sup>					
128-37-010 mg/m3 Mexico :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stards, 2002) :-Ceiling :Definition :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Netherlands / MAC-warder (10 december 2014) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, $000$ /052015) :STEL :Ceiling :Definition :Criteria :128-37-0TWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Switzerland (SUVAPROVE) :STEL :Ceiling :Definition :Criteria :128-37-0UN MEVLEValeur plafondNotations- Switzerland (SUVAPROVE) :VLEValeur plafondNotations128-37-010 i mg/m340 i mg/m3SSC UK / WEL (Workplace exposure limits, EH40/2005, 2011) :-SSC	- Malaysia :						
- Mexico :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stands, 2002) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Netherlands / MAC-warder (10 december 2014) :Ceiling :Definition :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, 04/06/2015) :Ceiling :Definition :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Switzerland (SUVAPROVER) :ULEValeur plafondNotations128-37-010 i mg/m340 i mg/m3SSCSSC- UK / WEL (Workplace exposure limits, EH4U/2005, 2011) :	CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stards; 2002) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Netherlands / MAC-watch (10 december 2014) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, $\sqrt{0}/02015$ ) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, $\sqrt{0}/02015$ ) :-Ceiling :Definition :Criteria :128-37-0TWA :STEL :Ceiling :Definition :Criteria :- Switzerland (SUVAPRC $\ge UT$ ) :VLEValeur plafondNotations128-37-010 i mg/m340 i mg/m3SSC UK / WEL (Workplace $\bowtie$ burget filts, $U/2005, 2011$ ) :-SSC	128-37-0	10 mg/m3	-	-	-	-	
128-37-010 mg/m320 mg/m3 New Zealand (Workplace Exposure stander, 2002) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Netherlands / MAC-water (10 december 2014) :CCriteria :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, 04/06/2015) :CCeiling :Definition :Criteria :128-37-0TWA :STEL :Ceiling :Definition :Criteria :128-37-010 (1) mg/m3 Switzerland (SUVAPRO 2017) :IO (1) mg/m3-SSCCASVMEVLEValeur plafondNotations128-37-010 i mg/m340 i mg/m3SSC- UK / WEL (Workplace xposure limits, EH40/2005, 2011) :	- Mexico :						
- New Zealand (Workplace Exposure standers, 2002) : CAS TWA : STEL : Ceiling : Definition : Criteria : 128-37-0 10 mg/m3 - Netherlands / MAC-warder (10 december 2014) : CAS TWA : STEL : Ceiling : Definition : Criteria : 128-37-0 10 mg/m3 - Slovenia (Uradni List, 04/06/2015) : CAS TWA : STEL : Ceiling : Definition : Criteria : 128-37-0 10 (I) mg/m3 - Switzerland (SUVAPRO 2017) : CAS VME VLE VLE Valeur plafond Notations 128-37-0 10 i mg/m3 40 i mg/m3 SSC - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :	CAS			Ceiling :	Definition :	Criteria :	
CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 $   -$ - Netherlands / MAC-wareter (10 december 2014) :Ceiling :Definition :Criteria :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 $   -$ - Slovenia (Uradni List, $\cup/Oc/2015$ ) : $   -$ CASTWA :STEL :Ceiling :Definition :Criteria :128-37-0TWA :STEL :Ceiling :Definition :Criteria : $-$ Switzerland (SUVAPRC $\cup$ UT7) : $   -$ CASVMEVLEValeur plafonNotations128-37-010 i mg/m3 $40$ i mg/m3 $ SSC$ $-$ UK / WEL (Workplace $\vdash$ posure limits, $\vdash$ H40/2005, $201$ ) : $ -$		e	-	-	-	-	
128-37-0       10 mg/m3         - Netherlands / MAC-waarde (10 december 2014) :         CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         128-37-0       10 mg/m3       -       -       -       -         - Slovenia (Uradni List, 04/06/2015) :       -       -       -       -         CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         - Slovenia (Uradni List, 04/06/2015) :       -       -       -       -         CAS       TWA :       STEL :       Ceiling :       Definition :       Criteria :         128-37-0       10 (1) mg/m³       10 (1) mg/m³       Criteria :       -       -         - Switzerland (SUVAPRO 2017) :       -       -       -       -       -         CAS       VME       VLE       Valeur plafond       Notations       -         128-37-0       10 i mg/m³       40 i mg/m³       SSC       -       -         - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :       -       SSC       -       -		ace Exposure star					
<ul> <li>Netherlands / MAC-warder (10 december 2014):</li> <li>CAS TWA: STEL: Ceiling: Definition: Criteria:</li> <li>128-37-0 10 mg/m3</li> <li>Slovenia (Uradni List, 04/06/2015):</li> <li>CAS TWA: STEL: Ceiling: Definition: Criteria:</li> <li>128-37-0 10 (1) mg/m3</li> <li>Notations: UVAPRO 2017):</li> <li>CAS VME VLE Valeur plafon Notations</li> <li>128-37-0 10 i mg/m3 40 i mg/m3</li> <li>SSC</li> <li>- UK / WEL (Workplace rouse limits, EH40/2005, 2011):</li> </ul>			STEL :	Ceiling :	Definition :	Criteria :	
CASTWA :STEL :Ceiling :Definition :Criteria :128-37-010 mg/m3 Slovenia (Uradni List, $\lor/0^2/015$ ) :CASTWA :STEL :Ceiling :Definition :Criteria :128-37-0TWA :10 (1) mg/m³-Criteria : Switzerland (SUVAPRU- UTT) :CASVMEVLEValeur plafonNotations128-37-010 i mg/m³40 i mg/m³-SSC UK / WEL (Workplacer limits, EH40/2005, 2017) :		-					
128-37-0       10 mg/m3       -	- Netherlands / MAC-w	aarde (10 decemb	per 2014) :				
- Slovenia (Uradni List, 04/06/2015) : CAS TWA : STEL : Ceiling : Definition : Criteria : 128-37-0 : 10 (I) mg/m <sup>3</sup> - Switzerland (SUVAPRO 2017) : CAS VME VLE VLE Valeur plafon Notations 128-37-0 10 i mg/m <sup>3</sup> 40 i mg/m <sup>3</sup> SSC - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :			STEL :	Ceiling :	Definition :	Criteria :	
CASTWA :STEL :Ceiling :Definition :Criteria : $128-37-0$ $10 (I) mg/m^3$ $10 (I) mg/m^3$ $VIE$ $VIE$ $VIE$ $VIE$ $VIE$ CASVMEVLEValeur plafondNotations $128-37-0$ $10 i mg/m^3$ $40 i mg/m^3$ $SSC$ $VK / WEL (Workplace reburner limits, EH40/2005, 2011) :VIEVIE$	128-37-0	10 mg/m3	-	-	-	-	
128-37-0       10 (I) mg/m³         - Switzerland (SUVAPRO 2017) :       VLE         CAS       VME       VLE       Valeur plafond         128-37-0       10 i mg/m³       40 i mg/m³       SSC         - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :       -       SSC	- Slovenia (Uradni List,	04/06/2015):					
- Switzerland (SUVAPRO 2017) : CAS VME VLE Valeur plafond Notations 128-37-0 10 i mg/m <sup>3</sup> 40 i mg/m <sup>3</sup> SSC - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :		TWA :		Ceiling :	Definition :	Criteria :	
CASVMEVLEValeur plafondNotations128-37-010 i mg/m³40 i mg/m³SSC- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :	128-37-0		10 (I) mg/m <sup>3</sup>				
128-37-0       10 i mg/m³       40 i mg/m³       SSC         - UK / WEL (Workplace exposure limits, EH40/2005, 2011) :       SSC	- Switzerland (SUVAPR	CO 2017) :					
- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :				Valeur plafond			
		-			SSC		
CAS TWA : STEL : Ceiling : Definition : Criteria :	- UK / WEL (Workplace	e exposure limits,	, EH40/2005, 2011	):			
	CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	

128-37-0	- ppm 10 mg/ m <sup>3</sup>	- ppm - mg/n	n <sup>3</sup>		
- USA / NIOSH REL (	National Institute	for Occupationa	l Safety and Hea	alth, Recommende	d exposure limits) :
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	10 mg/m3	-	-	-	-
- USA / NIOSH IDLH	(National Institut	e for Occupation	nal Safety and He	ealth, Immediately	Dangerous to Life or Health Concentrations) :
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
128-37-0	10 mg/m3				
- Croatia					

#### 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

## - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

General information :					
Physical state :	Fluid liquid.				
Important health, safety and environmental information					
pH :	Not relevant.				
Boiling point/boiling range :	Not specified.				
Flash Point : 94.00 °C.					
	Method for determining the flash point:				
	ASTM D 93-15 (Standard Test Methods for Flash Point by Pensky- Martens Closed Cup Tester).				
Vapour pressure (50°C) :	Not stated.				
Density :	1,039-1,047@20°C				
	Method for determining the density :				
	NF ISO 279:1999 (T75-111)				
Water solubility :	Insoluble.				
Melting point/melting range :	Not specified.				
Self-ignition temperature :	Not specified.				
Decomposition point/decomposition range :	Not specified.				
Index of refraction :	1,517-1,521@20°C				
	Method of determining the refractive index :				
	NF ISO 280:1999 (T75-112)				

#### 9.2. Other information

No data available.

## **SECTION 10 : STABILITY AND REACTIVITY**

### 10.1. Reactivity

No data available.

## 10.2. Chemical stability

This substance is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the substance can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

No data available.

#### **10.5. Incompatible materials**

No data available.

#### 10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

## **SECTION 11 : TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

Exposure to vapours from this solvent in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

May be harmful if swallowed. Repeated or prolonged contact with the substance may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible damage May cause an allergic reaction by skin contact. 11.1.1. Substances Acute toxicity : 4-METHOXY-ALPHA-METHYLBENZENEPROPANAL (CAS: 5462-06-6) LD50 = 4000 mg/kg Oral route : 11.1.2 Complex substance No toxicological data available for the substances. Monograph(s) from the IARC (International Agency for Research on Cancer) : CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans. **SECTION 12 : ECOLOGICAL INFORMATION** Toxic to aquatic life. The product must not be allowed to run into drains or waterways. 12.1. Toxicity 12.1.2 Complex substance No aquatic toxicity data available for the substances. 12.2. Persistence and degradability No data available. 12.3. Bioaccumulative potential No data available. 12.4. Mobility in soil No data available. 12.5. Results of PBT and vPvB assessment No data available. 12.6. Other adverse effects No data available. **SECTION 13 : DISPOSAL CONSIDERATIONS** The appropriate waste management of the substance and/or its container must be determined in accordance with local regulations. 13.1. Waste treatment methods Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

# 14.1. UN number

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- -
- 14.4. Packing group

#### -

- 14.5. Environmental hazards
- 14.6. Special precautions for user

## **SECTION 15 : REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- The following regulations have been used:
- Globally Harmonized System of Classification and Labelling of Chemicals (GHS), review no. 7 (2017)
- Container information:

No data available.

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) : NFPA 704, Labelling: Health=2 Instability=2 Instability/Reactivity=1 Specific Risk=none



### 15.2. Chemical safety assessment

No data available.

## **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the substance and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3 :

H303	May be harmful if swallowed.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.