

## **DC Power Supply**

# 180 ~ 360W Regulated Linear DC Power Supply TS-1000 / TS-1000X Series

#### Product description:

TS-1000/X series are linear DC power supplies with 2 channels, 95W to 185W output. TS-1000 series provide a simpler option of only 1 channel, 90W to 180W output. In constant voltage and current operations, the power supply provides high regulation and low ripple & noise. The output ON/OFF control and coarse/fine control enables safe and easy operation. TS-1000X series are widely used in applications of powering operational amplifier, push pull stages, logic circuit and definition systems.





- Constant voltage and constant current operations
- Auto CV and CC switch
- Output ON/OFF control
- High efficiency, light and compact design
- High power density
- Over load and reverse polarity protections
- Dual-color two digital panel meters





TS-1000X Series (Fixed output 5V/1A)

### Q Specifications

Model	TS-1303	TS-1303X	TS-1305	TS-1305X	TS-1603	TS-1603X	
Output Voltage	0 ~ 30V		0 ~ 30V		0 ~ 60V		
Output Current	0 ~ 3A	O ~ 3A			0 ~ 3A		
Constant Voltage Operation (CV I	mode)						
Line regulation	≤ 0.01%+3mV	≤ 0.01%+3mV			≤ 0.01%+3mV		
Load regulation	≤ 0.01%+3mV	≤ 0.01%+3mV		≤ 0.02%+5mV			
Ripple & Noise	≤3mVrms at Fred	: 5Hz ~ 1MHz					
Constant Current Operation (CC n	node)						
Line regulation	≤ 0.2%+3mA	≤ 0.2%+3mA					
Load regulation	≤ 0.2%+3mA	≤ 0.2%+3mA			≤ 0.2%+3mA		
Output Fixed							
Output Voltage		5V±1%		5V±1%		5V±1%	
Outut Current		1A		1A		1A	
Ripple & Noise	≤3mVrms						
Display							
Voltmeter	3 digit LED type						
Ammeter	3 digit LED type						
Resolution	100mV ~ 10mA						
Accuracy	±(1% Reading+ 2 di	±(1% Reading+ 2 digit)					
Operating environment	0°C ~ 40°C <80%F	0°C ~ 40°C <80%RH					
Storage environment	-10°C ~ 70°C, <70°	-10°C ~ 70°C, <70%RH					
Power Input	AC 110V/220V±109	AC 110V/220V±10%, 50/60Hz					
Dimension (WxLxD)	130mm x 160mm x	130mm x 160mm x 255mm.					
Weight	5 kg.		6kg.				

#### Ordering Information

#### **Standard Accessories:**

• User Manual

• Power cord

USB cable

• Software CD