



ProSeries™ Plus

Top and Side Mount Sand Filters

UP TO 130-GPM CAPACITY FOR DEMANDING
POOL ENVIRONMENTS



EXPERT LINE

ONLY FROM POOL PROS


3+ YEAR WARRANTIES

PARTS & LABOR COVERAGE

*When sold by a Totally Hayward® Partner. Exclusions, other terms and conditions may apply – visit hayward.com/expert for details.

PROSERIES™ PLUS FEATURES

- » **Integral top diffuser** ensures even distribution of water over the sand media bed. Internal piping provides smooth, free-flowing performance
- » **Efficient multilateral underdrain assembly** with precision-engineered, self-cleaning 360° slotted laterals provides totally balanced flow and backwashing
- » **Integral molded drain plug** drains the tank without losing sand
- » **Unitized, corrosion-proof tank** is molded of color-fast polymeric material for maximum durability
- » **Corrosion-proof base** provides strong, stable support
- » **Patented Service-Ease design** with unique folding ball joint provides easy access to lateral assembly
- » **Available in side- and top-mount models** for both residential and commercial pool applications



ADDITIONAL FEATURES (SIDE-MOUNT)

- » **Various control valve options** including a 2-position slide valve and a 6-position VariFlo® valve for selection
- » **Durable, easy-access flanged cover** for simple service and maintenance
- » **Manual and automatic air relief**



ADDITIONAL FEATURES (TOP-MOUNT)

- » **VariFlo® 6-position control valve** with easy-to-use lever-action handle for dialing any of 6 valve/filter functions
- » **Flanged clamp design** with 360° valve rotation to simplify plumbing

SPECIFICATIONS

Filter Type	High-rate sand: No. 20 silica sand (0.45 mm – 0.55 mm)		
Filter Tank	Molded Polymeric		
Underdrain	360° self-cleaning slotted laterals, precision installed in ball-joint assembly		
Support Base	Corrosion-proof thermoplastic		
Performance Range	99 to 130 GPM (375 to 492 LPM)		
	DIMENSIONS*	CONTROL VALVE OPTIONS	
Side-Mount	S311SXV - 31" W x 38 5/8" H (79 cm x 98 cm) S360SX - 36" W x 46" H (91 cm x 117 cm)	SP0710X62 - 1 1/2" FIP 6-position, VariFlo SP0715X62 - 2" FIP 6-position, VariFlo SP0410X602S - 2" SKT 2-position, slide valve	
Top-Mount	S360T2 - 36" W x 53" H (91 cm x 135 cm)	SP071620T - 2" FIP 6-position, VariFlo SP071621 - 2" FIP 6-position, VariFlo	

PERFORMANCE DATA

MODEL NUMBER	VALVE	EFFECTIVE FILTRATION AREA	DESIGN FLOW RATE**	MAXIMUM WORKING PRESSURE	TURNOVER		SAND REQUIRED
					8 HOURS	10 HOURS	
S311SXV	Side Valve	4.95 ft.² / 0.46 m²	99 GPM / 375 LPM	50 psi / 3.45 bar	47,520 gal / 180 kl	59,400 gal / 225 kl	350 lbs. / 159 kg
S360SX	Not Included	6.50 ft.² / 0.60 m²	130 GPM / 492 LPM	50 psi / 6.45 bar	62,400 gal / 236 kl	78,000 gal / 295 kl	700 lbs. / 318 kg
S360T2	Top Valve	6.50 ft.² / 0.60 m²	130 GPM / 492 LPM	50 psi / 6.45 bar	62,400 gal / 236 kl	78,000 gal / 295 kl	700 lbs. / 318 kg

*Above dimensions are for filter only. Add 14" (36 cm) for multi-port valve, add 7" (8 cm) for slide valve.

**Based upon 20 GPM per ft.² (815 LPM per m²). Maximum allowable NSF rating.

» hayward.com » 1-888-HAYWARD

Pumps » Filters » Heating » Cleaners » Sanitization » Automation » Lighting » Water Features » White Goods

Hayward, Hayward & Design, and the H logo, and VariFlo are registered trademarks and ProSeries is a trademark of Hayward Industries, Inc. © 2024 Hayward Industries, Inc.

LITPROPLSS24

HAYWARD
We Build Better.