






# **PROFLO 125T1- Single Element**

Model Number:


125T1



Storage Capacity (L) 130 (~34 Gallons)

Overall Height 1090
Overall Diameter 530

## Warranty\*



### No. of Adults & Children

Cont. Tariff



Adult icon can represent dishwasher or washing machine.

An adult icon does not represent a spa bath.

Heating Element	2.4 kW./ 240V.	3.6 kW. / 240V.	4.8 kW. / 240V.	6.0 kW. / 240V.
Service	10	15	20	25
(per element)	Amps	Amps	Amps	Amps
Recovery (per element)*	69 L/hr/30°C rise	103 L/hr/30°C rise	138 L/hr/30°C rise	172 L/hr/30°C rise

#### Specification

The water heater shall be a DUX<sup>®</sup> model 125T1 suitable for mains pressure water supply. The storage cylinder shall be lined with Duro-namel <sup>TM</sup> vitreous enamel suitable for operation up to 82°C. Internal anodic corrosion protection shall be provided. The water heater shall be completely insulated with high density polyurethane insulation and protected by a sealed Colorbond<sup>®</sup> metal case with access to the electrical element and thermostat. Electric immersion type, bolt mounted, heating element shall be fitted with an energy rating of \_\_\_\_\_Watts and controlled by an adjustable surface mounted thermostat complete with integral high temperature safety cut-out.

#### Local authority requirement

This product should be installed by a qualified plumber. Local Authority, Water Board and Building Regulations may apply to installation of this product, and you should consult the appropriate bodies on these requirements. Failure to comply may invalidate the product warranty.



<sup>\*</sup> Warranty terms as specified by the vendor of each country.