





PROFLO 400T1- Single Element

profic

Model Number: 400T1

Specifications

Storage Capacity (L) 415.6 (~110 Gallons)

Overall Height 1705
Overall Diameter 705

Warranty*



10 year tank warranty 1 year full parts & labour warranty*

No. of Adults & Children

Off Peak

Adult icon can represent dishwasher or washing machine. An adult icon does not represent a spa bath.

Heating Element	2.4 kW./240V.	3.6 kW. /240V.	4.8 kW. /240V.	6.0 kW. /240V.
Service (per element)	10 Amps	15 Amps	20 Amps	25 Amps
Recovery (per element)	69 L/hr/30°C rise	103 L/hr/30°C rise	138 L/hr/30°C rise	172 L/hr/30°C rise

Specification

The water heater shall be a DUX[®] model 400T1 suitable for mains pressure water supply. The storage cylinder shall be lined with Duro-namel TM vitreous enamel suitable for operation up to 82°C. Internal anodic corrosion protection shall be provided. The water heater shall be completely insulated with high density polyurethane insulation and protected by a sealed Colorbond®metal case with access to the electrical element and thermostat. Electric immersion type, bolt mounted, heating element shall be fitted with an energy rating of _____Watts and controlled by an adjustable surface mounted thermostat complete with integral high temperature safety cut-out.

Local authority requirement

This product should be installed by a qualified plumber. Local Authority, Water Board and Building Regulations may apply to installation of this product, and you should consult the appropriate bodies on these requirements. Failure to comply may invalidate the product warranty.



^{*} Warranty terms as specified by the vendor of each country.