



# Electric Solutions



## PROFLO 80T1- Single Element

Model : 80T1

Tank Size : 80 L

### Specifications



Storage Capacity (L)	88 (~23 Gallons)
Max. Water Supply Pressure	1100 kPa
Relief Valve Pressure	1400 kPa
Water Connections	RP20 20mm (¾" BSP) female
Overall Height	925
Overall Diameter	490
Net Weight (Empty Kg.)	40

### Warranty\*



10 year tank warranty

1 year full parts & labour warranty \*

No. of Adults & Children

Cont. Tariff



Adult icon can represent dishwasher or washing machine.

An adult icon does not represent a spa bath.

Heating Element	2.4 kW. / 240 V.	3.6 kW. / 240 V.	4.8 kW. / 240 V.	6.0 kW. / 240 V.
Service (per element)	10 Amps	15 Amps	20 Amps	25 Amps
Recovery (per element)	69 L/hr/30°C rise	103 L/hr/30°C rise	138 L/hr/30°C rise	172 L/hr/30°C rise

### •Specification

The water heater shall be a DUX® model 80T1 suitable for mains pressure water supply. The storage cylinder shall be lined with Duro-namel™ vitreous enamel suitable for operation up to 82°C. Internal anodic corrosion protection shall be provided.

The water heater shall be completely insulated with high density polyurethane insulation and protected by a sealed Colorbond® metal case with access to the electrical element and thermostat. Electric immersion type, bolt mounted, heating element shall be fitted with an energy rating of \_\_\_\_\_ Watts and controlled by an adjustable surface mounted thermostat complete with integral high temperature safety cut-out.

#### •Local authority requirement

This product should be installed by a qualified plumber. Local Authority, Water Board and Building Regulations may apply to installation of this product, and you should consult the appropriate bodies on these requirements. Failure to comply may invalidate the product warranty.

\* Warranty terms as specified by the vendor of each country.



Australian Products