

Shower unit

WS 35 E, WS 45 E

DATA PRODUCT

Model	:	WS 35 E	WS 45 E
Product Code	:	232715	232716
Dimension (HxWxD)	:	200 x 326 x 79 mm.	
Box Dimension (HxWxD)	:	503 x 230 x 140 mm.	
Weight of Product	:	1.40 kg.	2.00 kg.
Weight overall	:	2.00 kg.	2.06 kg.



Shower unit

WS 35 E, WS 45 E

PACKAGING BOX




Shower unit

WS 35 E, WS 45 E

PATTERN PACKAGING BOX




BACK VIEW



RIGHT VIEW



TOV VIEW



LEFT VIEW



FRONT VIEW



BOTTOM VIEW

Shower unit

WS 35 E, WS 45 E

PRODUCT BARCODE



WS 35 E
232715



WS 45 E
232716

Shower unit

WS 35 E, WS 45 E



FEATURES

- Luxury design
- Exact temperature adjustment with single stepless knob control
- Quick and simple to install
- Easy and safe to operate
- Anti-scalding prevention with hi-tech double action auto thermostat
- ELSD (Electric Leakage Safety Device) protection against electricity leakage
- Water/splash-proof to IP 25 electrical safety standard
- Maintenance-free copper tank
- 5-in-1 shower setting
- Works well even in low water pressure

Shower unit

WS 35 E, WS 45 E

TECHNICAL DATA

Product Name	WS 35 E	WS 45 E
Product Code	1211-232715	1211-232716
Barcode Product	 8 854685 003946	 8 854685 003953
Type	WS 35 E	WS 45 E
Design	Open outlet	
Min. inlet water pressure	0.15 bar / 0.015 MPa	
Max. inlet water pressure	5 bar / 0.5 MPa	
Water connection	G 1/2" (External Thread)	
Electrical connection	1/N/PE/AC 220...240 V.	
Dimension (W x H x D) (mm.)	200 x 326 x 79	
Weight (kg)	1.4	
Recommended circuit breaker (A.)	20	25
Recommended cable size (Sqmm.)	2.5 - 4	
Rated power (kW) Rated current (A)	kW - A	kW - A
	220 V	220 V
	3.5 - 15.9	4.5 - 20.5
	230 V	230 V
	3.8 - 16.5	4.9 - 21.3
	240 V	240 V
	4.2 - 17.5	5.4 - 22.5