

Drop-in Cooker (with Metal Casing)

NBK35



Specification

Electricity	NBK35	220V, 60Hz, 1PH	Power Consumption	NBK35	3500 W		
	NBK35-A	208~240V, 50/60Hz, 1PH		NBK35-A	3300 W		
	NBK35-E	220~240V, 50/60Hz, 1PH		NBK35-E	3500 W		
	NBK35-CE1	220~240V, 60Hz, 1PH		NBK35-CE1	3000 W		
	NBK30-J	200V, 50/60Hz, 1PH		NBK30-J	3000 W		
Power Connection	Plug type		Max Current	15 A			
Conversion to Calory	3024 Kcal/h						
Warming	H1 ~ H7 (7 steps)		Heating	1 ~ 10 (10 steps)			
Output per Warming Steps	H1	H2	H3	H4	H5	H6	H7
	40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh
Dimension / Weight	Product: 296 X 370 X 80 (mm) / 6.5kg Package: 490 X 360 X 180 (mm) / 7.1kg						
Controller Type	Jog dial, Capacitive button (separated from the unit)						
Power Cable	660 mm		Controller Cable	660 mm			
Cookware Diameter	min : Ø125mm max : Ø240mm		Loadable Weight	30 Kg			
Recommendation	Hotpot, Shabu shabu, Built-in on dining table						
Functions & Features	<input checked="" type="checkbox"/> Metal body makes the unit more durable						
	<input checked="" type="checkbox"/> Safety						
	- No vessel : "00"						
	- Over current indication : "E1"						
	- Over voltage indication : "E2" (Above 265V)						
	- Low voltage : "E3" (Below 180V)						
	- Over heated product indication : "E4" (IGBT heat sink temperature above 85°C)						
	- Top glass overheated (empty vessel) : "E6" (Top surface temperature above 260°C)						
	- Unstable power indication: "E7"						
	- Defective PCB indication : "E8"						
- Defective Working Coil indication : "E9"							
<input checked="" type="checkbox"/> Timer Setting							
- Between 1sec - 720min (12hr)							
Warranty	1 year (to be charged in case of user's negligence)						

#503, Hanam Venture Center, Geomdansen-ro 239, Hanam-si, Gyeonggi-do, 13023 / Tel : +82-31-793-5895 / FAX : +82-31-793-5862

DIPO INDUCTION RANGE / www.dipoinduction.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
Control	Control Cut
<p>Control Wire Length = 660mm</p>	
<p>#503, Hanam Venture Center, Geomdansan-ro 239, Hanam-si, Gyeonggi-do, 13023 / Tel : +82-31-793-5895 / FAX : +82-31-793-5862</p> <p>DIPO INDUCTION RANGE / www.dipoinduction.com</p> <p>COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.</p>	