

# DC-D4516WRX 4.0mm

## H.265 5M IR Dome Camera / NDAA Compliant



- Easy installation with DirectIP NVR
- micro SD/SDHC/SDXC
- IK10 / IP67 supports
- True wide dynamic range (WDR)
- Supports ONVIF
- 5MP (2592x1944) resolution
- Two-way audio
- PoE (IEEE 802.3af Class 3)
- IR LED (Distance : 30m / 98.4ft)
- Fixed-focal lens (f=4.0mm)
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation

### SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	4.0mm
Aperture	F2.15
Iris Control	Fixed Iris
Angular Field of View	79.2o(H) 56.6o(V) 103o(D)
Min. Illumination	COLOR : 0.15 lux @ F2.15 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 - 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Pan/Tilt/Rotate	
Pan Range	-170° - 170°
Tilt Range	-5° - 67.5°
Rotate Range	-109° - 109°
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960x 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE (IEEE 802.3af Class 3)
Power Consumption	PoE, (IEEE 802.3af Class 3), 7.6W
Approval	FCC, CE, KC
Mechanical	
Dimensions	Ø120.6 x 92.9mm(Ø4.75" x 3.66")
Weight	0.48kg (1.06lb)



### PRODUCT IMAGE



























### DIMENSIONS



### ACCESSORIES (OPTIONAL)



# ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION	
DC-D4516WRX 4.0mm	WALL	 <b>JUNCTION BOX</b> Model: DA-JB4700	
		or	
		 <b>MOUNT ADAPTER</b> Model: DA-MA4300   <b>WALL MOUNT</b> Model: DA-WM2050	
	CELLING	 <b>JUNCTION BOX</b> Model: DA-JB4700	
		or	
		 <b>CEILING MOUNT</b> Model: DA-CM2050   <b>MOUNT ADAPTER</b> Model: DA-MA4300	
	POLE	 <b>POLE MOUNT</b> Model: DA-LM2000   <b>MOUNT ADAPTER</b> Model: DA-MA4300   <b>WALL MOUNT</b> Model: DA-WM2050	
		or	
		 <b>JUNCTION BOX</b> Model: DA-JB4700   <b>POLE MOUNT</b> Model: DA-LM2000	
		CORNER	 <b>MOUNT ADAPTER</b> Model: DA-MA4300   <b>CORNER MOUNT</b> Model: DA-RM2000   <b>WALL MOUNT</b> Model: DA-WM2050
			or
			 <b>JUNCTION BOX</b> Model: DA-JB4700   <b>CORNER MOUNT</b> Model: DA-RM2000