

DR-1508P


DirectIP 1500 Series Full HD Recorder / NDAA Compliant



- Total incoming throughput 100Mbps
 - Easy to install, set-up, and play with DirectIP cameras
- Up to 240ips 8MP real-time recording
 - Built-in 8 channel PoE Switch
- Up to 240ips live display
 - Supports one click network configuration through FEN service

SPECIFICATIONS

Video	
Video Inputs	8 IP Channels
Max. Incoming Throughput	100Mbps
Supported Camera	DirectIP
Video Outputs	1 HDMI, 1 VGA
Display Resolution	1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 240ips
Digital Zoom	x2 ~ x12
Recording	
Max. Throughput	40Mbps, 240ips@8MP
Recording Resolution	Up to 8MP (Depending on IP Camera)
Video Compression	H.265, H.264
Recording Mode	Time-lapse, Event, Pre-event, Panic
Trigger Event	Motion Detection, Trip-zone, Tampering, Video Loss, Etc.
Playback	
Performance	4ch Full HD Synchronous Playback
Search Mode	Time-lapse, Event Log
Digital Zoom	x2 ~ x12
Storage	
HDD	SATA x 1
Network	
Client Connection	Fast Ethernet (Client) x1
Video In Connection	Fast Ethernet (IP Camera) x8
Transmission Speed	20Mbps
PSE Power	PoE (IEEE 802.3at Class 4) Supported 4 Ports, 50W
Event Notification	Email (MP4), Callback to Remote S/W, Push Notification (IDIS Mobile)
Interface	
USB	USB 2.0 x 2
User Interface	Mouse
General	
Operating System	Embedded Linux
Environmental	
Operating Temperature	0°C to 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Consumption	54-56V-, 1.28-1.24A, 69W MAX
Approval	KC, CE, FCC
Mechanical	
Unit Dimensions (W x H x D)	205mm x 44.5mm x 216.4mm (8.07" x 1.75" x 8.52")
Unit Weight	1.2kg (2.65 lb) (with 1 HDD)



PRODUCT IMAGE



DIMENSIONS

