

TR-1504

DirectCX 4channel H.265 Recorder / NDA Compliant



- Supports Multi Standard Analog Camera
- Up to 5MP resolution support
- Long transmission distance over coax cable
- Up to 120ips Full HD recording
- Full HD Display with HDMI and VGA output
- Supports OSD control over Coax
- H.265 encoding , Intelligent Codec Support
- Supports CVBS Spot Monitor
- Supports one click network configuration through FEN service

SPECIFICATIONS


Video	
Video Inputs	4 BNC (Multistandard Analog)
Supported Camera	5MP20, 5MP12, 4MP30, 4MP25, 4MP15, 3MP18, 1080P30, 1080P25, 720P30, 720P25, CVBS(NTSC/PAL)
Video Outputs	1 HDMI, 1 VGA, 1 BNC(Spot)
Display Resolution	HDMI / VGA : 1920 x 1080, 1280 x 1024 Composite : 720x480(NTSC) , 720x576(PAL)
Display Speed	Up to 120ips
Digital Zoom	x2 - x7
Recording	
Recording Resolution	2560x1944, 2560x1440, 1920x1536, 1920x1080, 1280x720, 960x480, 720x576, 720x480, 960x288, 960x240, 640x360, 720x288, 720x240, 480x288, 480x240, 360x288, 360x240
Video Compression	H.265, H.264, Intelligent Codec
Recording Mode	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	Alarm in, Motion detection, Video loss
Playback	
Performance	4ch synchronous playback
Search Mode	Time-lapse, Event log
Digital Zoom	x2 - x7
Storage	
HDD	SATA x 1
Network	
Client Connection	Fast Ethernet x1
Transmission Speed	30ips@Full HD per channel, same as recording stream
Event Notification	Email (attach clip cbf, mp4), Callback to Remote S/W, Push notification (IDIS Mobile)
Two-way Audio	Yes
Interface	
Audio In / Out	1 RCA / 1 RCA + 1 HDMI
Alarm In / Out	4 In / 1 Relay Out
USB	USB 2.0 x 2
User Interface	Mouse, Network Remote Keyboard
General	
Operating System	Embedded Linux
Environmental	
Operating Temperature	0°C to 40°C (32°F - 104°F)
Operating Humidity	0% - 90%
Electrical	
Power Input	(a) US/JP Adaptor Input : 100-240V AC, 50/60Hz, 1.0A, Output : 12V DC, 3A (b) UK, ETC Adaptor Input : 100-240V AC, 50/60Hz, 1.2A, Output : 12V DC, 3A (c) KR Adaptor Input : 100-240V AC, 50/60Hz, 0.8A, Output : 12V DC, 3A
Power Consumption	12V-, 0.75A, 9W
Approval	FCC, KC
Mechanical	
Unit Dimensions (W x H x D)	205mm x 44.5mm x 223.4mm(8.07" x 1.75" x 8.80")
Unit Weight	1.3kg(0.7lb) (with 2TB HDD)



PRODUCT IMAGE



DIMENSIONS



- ① Power In Port
- ② USB Ports
- ③ Network Port
- ④ HDMI Out Port
- ⑤ VGA Out Port
- ⑥ Alarm Connection
- ⑦ SPOT
- ⑧ Audio In / Out
- ⑨ Video Input