

DR-2208P

- Total incoming throughput 116Mbps
- Up to 240ips Full HD real-time recording
- Up to 240ips live display
- Easy to install, set-up, and play with DirectIP cameras
- Built-in 8 channel PoE switch
- Expandable up to 36TB using eSATA storage
- Supports one click network configuration through FEN service
- Supports third-party cameras (Axis, Panasonic, ONVIF)





SPECIFICATIONS

| VIDEO | |
|-----------------------------|---|
| Video Inputs | 8 IP Channels |
| Max. Incoming Throughput | 116Mbps |
| Supported Camera | DirectIP, Axis, Panasonic, ONVIF |
| Video Outputs | 1 HDMI, 1 VGA |
| Display Resolution | 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 |
| Display Speed | Up to 240ips |
| Digital Zoom | x2 ~ x12 |
| RECORDING | |
| Max. Throughput | 64Mbps, 240ips @ Full HD |
| Recording Resolution | Up to 12MP (Depending on IP Camera) |
| Compression | H.264 |
| Recording Mode | Time-lapse, Event, Pre-event, Panic |
| Trigger Events | Alarm In, Audio Detection, Motion Detection, Trip Zone, Tampering, Video Loss |
| PLAYBACK | |
| Performance | 4ch Full HD Synchronous Playback |
| Search Modes | Time-lapse, Event Log, Thumbnail, Motion, Text-in |
| Digital Zoom | x2 ~ x12 |
| STORAGE | |
| HDD | SATA x 2, eSATA x 1 (Up to 6TB Capacity for Each Disk) |
| Total Capacity | 36TB = 6TB x (2 + 1 x 4) |
| NETWORK | |
| Client Connection | Gigabit Ethernet (Client) x 1 |
| Video In Connection | Fast Ethernet (IP Camera) x 8 + Gigabit Ethernet (Ext) x 1 |
| Transmission Speed | 20Mbps / 50Mbps (BRP Mode) |
| Camera Power | PoE (IEEE 802.3at Class 4) Supported 8 Ports, 50W |
| Remote Data Export | IDIS Player, AVI, JPG |
| Event Notification | Email (Attach Clip (.cbf) .MP4), Callback to Remote S/W, Push Notification (IDIS Mobile), SNS (Twitter) |
| Two-way Audio | Yes |
| Client Viewer | IDIS Center, IDIS Mobile, IDIS Web, IDIS Solution Suite |
| INTERFACE | |
| Audio In / Out | Local (NVR) : - / 1 RCA + 1 HDMI IP Camera : 8 / 8 (Depending on IP Camera) |
| Alarm In / Out | Local (NVR) : 4 / 1 IP Camera : 8 / 8 (Depending on IP Camera) |
| Alarm Reset In | - |
| Serial Interface | RS232 (Terminal Block) |
| USB | USB 2.0 x 1, USB 3.0 x 1 |
| User Interface | Mouse, IR Remote Control, Network Remote Keyboard |
| GENERAL | |
| Operating System | Embedded Linux |
| Unit Dimensions (W x H x D) | 300mm x 62mm x 231mm (11.8" x 2.4" x 9.1") |
| Unit Weight | 2.3kg (5.1lb) (With 1 HDD) |
| Working Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Operating Humidity | 0% ~ 90% |
| Power Input | DC 12V 2.1A (for NVR), DC48V 1.08A (for PSE) |
| Power Consumption | Max. 25.2W (for NVR), Max. 52W (for PSE) |
| Approvals | FCC, CE, KC, PSE |

DIMENSIONS

(Unit - mm)



- | | |
|------------------------|--------------------------|
| 1 Factory Reset Button | 7 Video In / Ext. Port |
| 2 Audio Port | 8 Network Port |
| 3 VGA Out Port | 9 Alarm Connection Ports |
| 4 HDMI Out Port | 10 RS-232 Port |
| 5 eSATA Port | 11 Power In Port (12V) |
| 6 Video In / PoE Ports | 12 Power In Port (48V) |

ACCESSORIES (OPTIONAL)



DH-2212PF



DA-ES1104