

ATMOCE

Single-phase M-Combiner Lite

MC100L



Data Sheet

Key Features

Safety & Reliability

- IP65 design for indoor and outdoor installations
- Reliability verification in extreme scenarios
- Reinforced insulation for improved safety

High Power Capability

- Max. PV power of 7.5 kW
- Max. battery capacity of 14 kWh

Flexibility & Intelligence

- Remote management of home electricity
- Bi-directional communication between devices and ATMOCE-Cloud
- All-in-one app to guide the installation and configuration

Easy Installation

- Pre-installed and pre-connected
- Easy system activation by using the ATMOZEN app
- Lightweight design



Items	Unit	MC100L
What's in the combiner		
SPD		1 × unit, In: 20 kA, 2-pole
SPD breaker		1 × unit, 25 A, 2-pole
PV-side breaker ^a		1 × unit, 32 A, 2-pole
Grid-side breaker		1 × unit, 63 A, 2-pole, RCD 100 mA
Battery-side breaker		1 × unit, 63 A, 2-pole
Battery CT		1 × CT, accurate up to 0.1%
Consumption CT interface		1 × CT signal interface, accurate up to 0.1%
Electrical parameters		
Grid setup		Single-phase
Nominal voltage	V	220/230/240
Operating voltage range (L to N)	V	176 to 276
Nominal frequency	Hz	50/60
Extended frequency range	Hz	45 to 65
Max. PV branch		1
Max. battery current	A	63
Max. battery capacity	kWh	14
AC surge protection		TYPE II
Overvoltage category		III
Mechanical parameters		
Dimensions (W x H x D)	mm	337 × 237 × 99
Weight	kg	2.4
Ambient temperature range	°C	-30 to 50
Cooling		Natural convection
Enclosure environmental rating		Outdoor, IP65
Power cable sizes ^b	mm ²	PV side: 2.5 to 6 Grid side: 6 to 10 Battery side: 4 to 10
Communication cable sizes	mm ²	0.25 to 0.75
Communication		PLC, Wi-Fi, BLE, ETH, CAN
Noise	dB	<25
Altitude	m	3000
Protection class		II
Pollution degree		III
Communication interfaces		
PV side	PLC	Support
Grid side		1 × interface for consumption CT
Battery side	CAN	Support

Items	Unit	MC100L
Load side	ETH	1 × interface, 100 Mb/10 Mb auto-adaptability
Atmoce-Cloud	Wi-Fi	2.4 GHz
	ETH	1 × interface, 100 Mb/10 Mb auto-adaptability
Atmozen app	BLE	2.4 GHz
Indicators		3 × LEDs

Compliance		

Safety		IEC 61439-1/-2
Health		IEC 62311
EMC		EN 301 489-1/-17, IEC 61000-6-1/-2/-3/-4
Radio spectrum		EN 300 328
PLC		EN 50065-1/-2

- a. The standard configuration of the PV-side breaker is 32A, which can be replaced with a 50A rated circuit breaker, supporting a maximum of 7.5kW.
- b. Refer to the local electrical regulations to select the cable size.