

THERMOBREAK®

High-performance
Thermal & Acoustic Insulation

Thermobreak®
LS FOIL TAPE



A Fully Engineered System.

Thermobreak LS Foil Tape is an essential component of the Thermobreak insulation system. With a reinforced aluminium foil facing and an acrylic pressure-sensitive adhesive, it ensures the ultimate performance from your insulation system.

≤ 0.05

Very low surface emittance.

80°C

High temperature range.

Class 0

Superior fire performance tested to global standards.

50 Meters

Convenient 50m length rolls.

Technical Data

Material	Aluminium foil/glass scrim reinforcement/pressure sensitive adhesive/silicone coated release liner
Operating Temperature Range	-40°C to 80°C -40°F to 176°F
Emittance (ASTM C1371)	≤ 0.05
Tensile Strength (ISO 1421)	MD = 8.2 kN/m CD = 7.6 kN/m
BS 476 (Part 6 & 7)	Class 0
REACH Directives (1907/2006/EC)	Complies

*Technical data may be plant specific. Please consult the Thermobreak LS Foil Tape Technical Data Sheet for full technical data.

Size availability

Width		Length		Rolls Per Carton
Metric	Imperial	Metric	Imperial	
50mm	2"	50m	164'	24
75mm	3"	50m	164'	16

*Other sizes available upon request



www.thermobreak.com

Sekisui Foam Australia
1-5 Parraweena Road
Taren Point
NSW 2229
Australia

+61 2 9525 9880
info@sekisuifoam.com.au
www.sekisuifoam.com.au

Thai Sekisui Foam
700/379 Moo 6
Tumbol Don Hua-loh, Amphur Muang
Chonburi 20000
Thailand

+66 3821 3219 - 26
info@thaisekisui.co.th
www.thaisekisui.co.th

THERMOBREAK®

SEKISUI
FOAM INTERNATIONAL