



FEATURES

- Support H.264+/H.264
- Support AHD/TVI/CVI/CVBS/IP Cameras
- Support AHD/TVI/CVI cameras up to 2MP
- Support Smart Detection & Smart Playback
- Support Time Division & Instant Playback
- Support Google Drive & Dropbox Cloud storage
- Support Cloud upgrade
- Support Event stream
- Extra IP Channels

SPECIFICATION

System	
Model	WXR72104N
Chipset	Hi3520Dv200
Video and Audio Input	
Video Input	4ch BNC interface(1.0Vp-p, 75 Ω)
TVI	1080P, 720P
CVI	1080P, 720P
AHD	1080P, 720P
IPC	2CH 2MP in default mode; Up to 6ch 2MP in full IP mode
CVBS	Support
Audio Input	1-ch, RCA(2.0 Vp-p, 1 kΩ)
Two way talk	1-ch, multiplex with Audio Input(RCA)
Video and Audio Output	
HDMI	1ch, resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
CVBS output	NA
Audio Output	1-ch, RCA (Linear, 1kΩ)
Recording	
Compression	H.264+/H.264
Resolution	Playback in priority: 4ch 1080P Lite@15fps; 960H1/D1/CIF real time Recording in priority: 4ch 1080P lite/960H1/D1/CIF real time
Frame rate	1fps-25fps(PAL)/30fps(NTSC)
Video Bit Rate	11Kbps-2707Kbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Bit Rate	64Kbps
Playback & Backup	
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
Playback Number	4ch Playback
Backup Mode	USB Device/Network
Smart Function	
Smart Detection for Analog	1CH line crossing detection, Area Intrusion
Smart Detection for QV IPC	line crossing detection ,area Intrusion
Smart Playback for Analog	line crossing detection, Area Intrusion
Smart Playback for QV IPC	Motion detection, line crossing detection, Area Intrusion
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP, TCP/IP, IPv4, UPnP, Onvif2.6, RTSP, RTCP, UDP, SMTP, SNMP, Multicast, IGMP, NTP, DHCP, DNS, DDNS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)
Hard Disk	
SATA	1 HDD
Capacity	Up to 8TB capacity for each HDD
External Interface	
Serial Interface	NA
USB Interface	2 × USB
General	
Power Supply	DC12V, 2A
Power Consumption	≤10W(without HDD)
Working Environment	-10°C~+55°C / 10%-90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight(with Out HDD)	1.5kg

