

General Purpose, Single Acting,
Spring Return.

Capacity: 5-100 Tonne

Complies with ASME B30.1. High strength steel for durability and increased safety.

Hardened and chromed piston increase durability and reduces wear.

Collar threads, piston threads and base mounting holes enable easy fixturing.

Heavy-duty piston return springs.

High quality EAB-201 quick couplers.

Environmentally friendly painting process provides a durable anti-corrosion finish.



รุ่น	กำลังอัด (ตัน)	ระยะยียด (มม.)	ความสูงกระบอก	ขนาด (มม.)	ใช้รวมปั๊มมือ	น้ำหนัก (กก.)
ES-50	5	16	42	59 X 42	CB-700C	0.8
ES-51	5	25	110	38	CB-700C	1
ES-53	5	75	165	38	CB-700C	1.3
ES-55	5	127	215	38	CB-700C	1.7
ES-57	5	177	273	38	CB-700	2.1
ES-59	5	232	323	38	CB-700	2.3
ES-101	10	26	89	57	CB-700C	1.7
ES-102	10	54	121	57	CB-700C	2.2
ES-104	10	105	171	57	CB-700C	2.9
ES-106	10	156	247	57	CB-700C	4.1
ES-108	10	203	298	57	CB-700	4.9
ES-1010	10	257	349	57	CB-700	5.6
ES-1012	10	304	400	57	CB-700	6.4
ES-1014	10	356	450	57	CB-700	7.2
ES151	15	25	124	70	CB-700	3.2
ES152	15	51	149	70	CB-700	3.7
ES-154	15	101	200	70	CB-700	5
ES-156	15	152	271	70	CB-700	6.5
ES-158	15	203	322	70	CB-700A	7.7
ES-1510	15	254	373	70	CB-700A	8.7
ES-1512	15	305	423	70	CB-700A	9.8
ES-1514	15	356	474	70	CB-700A	10.8
ES-251	25	26	134	86	CB-700	5.3
ES-252	25	50	165	86	CB-700	6.2
ES-254	25	102	215	86	CB-700	8
ES-256	25	158	273	86	CB-700A	10.3
ES-258	25	210	323	86	CB-700A	12.1
ES-2510	25	261	374	86	CB-700A	14.1
ES-2512	25	310	425	86	CB-700A	15.5
ES-2514	25	362	476	86	CB-700A	17.4
ES-308	30	300	387	105	CB-700A	21.5
ES-502	50	51	176	127	CB-700	14.4
ES-504	50	102	227	127	CB-700A	18.1
ES-506	50	159	282	127	CB-700A	22.2
ES-5013	50	337	260	127	CB-700A	34.3
ES-756	75	156	285	146	CB-700A	30.5
ES-7513	75	333	492	146	CB-630A	50.3
ES-1006	95	168	357	177	CB-630A	59.7
ES-10010	95	260	449	177	CB-630A	72.9

Features

- 1 Mid-empty designed and wide apply.
- 2 Principal axis have the function of auto-reback.
- 3 Each type contains the quick coupler.
- 4 Prevent rust with grill lacquer.

