



Low Height, Single Acting Cylinder

Capacity:
5-150T
Stroke:
5-115mm
Max. Pressure:
700 Bar



รายละเอียด

Hydraulic cylinders ESL – series ครอบคลุมไฮดรอลิกเหมาะกับการยกชิ้นงานงานต่างๆไปมีให้เลือกตั้งแต่ 10 – 150ตัน
Use in confined spaces.
Complies with ASME B30.1. High strength steel for durability and increased safety.
Heavy-duty piston return spring.
High quality EAB-201 quick couplers.
Environmentally friendly painting process provides a durable anti-corrosion finish

รุ่น	กำลังอัด (ตัน)	ระยะยียด (มม.)	ความสูงกระบอก	ขนาด (มม.)	ใช้ร่วมปั๊มมือ	น้ำหนัก (กก.)
ESL-101	10	38	88	69	CB-700C	4
ESL-201	20	45	98	92	CB-700C	5
ESL-302	30	62	117	102	CB-700C	7
ESL-502	50	60	122	124	CB-700	10
ESL-1002	100	57	141	165	CB-700	19

Features

- 1 It has the characteristic of low collapsed height, if the requirement of stroke need to be higher than ESL- series is suit for this case.
- 2The surface of principle axis is finished with chrome plate to protect the using of longevity of the product
- 3 Plunger has the function of retracting automatically WRC rotary head, can work in bevel.

