

# **MATERIAL SAFETY DATA SHEET**

**TURBO** Isopropanol alcohol

# **SECTION 1 – PRODUCT AND COMPANY INDENTIFICATION**

PRODUCT NAME	TURBO Isopropanol alcohol	
MANUFACTURER	Turbo Paint, NDW Chemical Co., Ltd.	
TELEPHONE	(662) 750 6804	
FAX	(662) 312 1707	
EMAIL ADDRESS	marketing.ndw@gmail.com	
ADDRESS	87/1 Moo 11 Thanasit, Theparak Rd., Bangplee, Samutprakarn 10540 Thailand	

# **SECTION 2 – INFORMATION ON INGREDIEANTS**

NAME	CAS No.	UN No.	%	RISK PHRASES
Isopropanol alcohol	67-63-0		100	

# **SECTION 3 – HARZARDS IDENTIFICATION**

Flammable

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful by inhalation and in contact with skin.

# **SECTION 4 – FIRST AID MEASURES**

Eye Contact	Flush with water immediately for 15 minutes. Consult a physician.
Skin Contact	Flush skin with plenty of water while removing contaminated clothing
	and shoes. Launder clothing before reuse. If rash or irritation develops,
	consult a physician.
Inhalation	Remove to fresh air. Administer oxygen if necessary. Consult a physician
	if symptoms persist or exposure was severe.
Ingestion	If swallowed do not induce vomiting. Seek immediate medical attention.

# SECTION 5 – FIRE AND EXPLOSION HAZARD DATA







**TURBO** Isopropanol alcohol

# Extinguishing Media Recommended: alcohol resistant foam, CO2, powders, water spray. Recommendations Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

### **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

Personal Precautions Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
Spill Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

# SECTION 7 – HANDLING AND STORAGE

Handling Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty containers. Avoid breathing vapors or spray mist.
Storage Keep away from heat, sparks, open flames and oxidizing agents. Keep containers closed. Store in a cool, dry place with adequate ventilation.

# **SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

Engineering MeasuresProvide forced air ventilation when applying in confined spaces.Respiratory ProtectionUnlikely to be necessary. Use approved chemical filter respirator.EyesSafety glasses or chemical eye goggles are suggested.





Effective Date:17/03/22



# MATERIAL SAFETY DATA SHEET

**TURBO** Isopropanol alcohol

Hands	Non-natural, non-butyl rubber gloves are recommended.
Skin	Use protective clothing. Remove contaminated clothing and wash the affected
	with soap and water.

# **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Liquid
Clear
Alcohol odor
0.785
-
Soluble
-89.5 C (-129.1 F)
82 C (180 F)
12 C (53.6 F)
Soluble

# SECTION 10 – STABILITY AND REACTIVITY

StabilityStable under recommended storage and handling conditions (see section 7).Hazardous Decomposition Productscarbon monoxide, carbon dioxide, smoke, oxides of nitrogen.Strong exothermic reactionsoxidizing agents, strong alkalis, strong acids.

# SECTION 11 – TOXICOLOGICAL INFORMATION

Not Available

**SECTION 12 – ECOLOGICAL INFORMATION** 

Prolonged or repeated contact may cause chronic dermatitis. Appreciable evaporation to air is expected in the environment.







# MATERIAL SAFETY DATA SHEET

**TURBO** Isopropanol alcohol

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

### Method of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14 – TRANSPORT INFORMATION**

Proper shipping nameISOPROPANOLPacking GroupIIHazard Class-UN No.1219

# SECTION 15 – REGULATORY INFORMATION

Highly flammable

Harmful by inhalation, in contact with skin and if swallowed

Irritating to eye and skin

Keep out of reach of children

Keep away from sources of ignition - No Smoking

Do not breathe gas/fumes/vapour/spray

Avoid contact with skin and eyes

Wear suitable protective clothing, gloves and eye/face protection

**SECTION 16 – OTHER INFORMATION** 

This document could not be used for certifying the quality of the product.

This document presents the information of the product and to be used for safety only.

**Remark** The above information and data given here is based on test, experiences that









TURBO Isopropanol alcohol

are considered reliable and believed to be accurate. For more information, please contact R&D department of NDW Co., Ltd.



