

TURBO Paint Remover

SECTION 1 – PRODUCT AND COMPANY INDENTIFICATION

PRODUCT NAME TURBO Paint Remover

MANUFACTURER Turbo Paint, NDW Chemical Co., Ltd.

TELEPHONE (662) 750 6804 **FAX** (662) 312 1707

EMAIL ADDRESS marketing.ndw@gmail.com

ADDRESS 87/1 Moo 11 Thanasit, Theparak Rd., Bangplee, Samutprakarn 10540 Thailand

SECTION 2 – INFORMATION ON INGREDIEANTS

| NAME | CAS No. | UN No. | % | RISK PHRASES |
|--------------------|------------|--------|------|--------------|
| 1-Isobutanol | 25265-77-4 | | <5 | |
| Ammomium Hydroxide | 1336-21-6 | | <0.2 | |
| Diuron | 330-54-1 | | <0.1 | |

SECTION 3 – HARZARDS IDENTIFICATION

Flammable

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful by inhalation and in contact with skin.

SECTION 4 – FIRST AID MEASURES

Eye Contact Flush with water immediately for 15 minutes. Consult a physician.

Skin Contact Flush skin with plenty of water while removing contaminated clothing

and shoes. Launder clothing before reuse. If rash or irritation develops,

consult a physician.

Inhalation Remove to fresh air. Administer oxygen if necessary. Consult a physician

if symptoms persist or exposure was severe.

Ingestion If swallowed do not induce vomiting. Seek immediate medical attention.

reen Industry
กระทรวงอุตสาหกรรม

UKAS Medication of the control of th



TURBO Paint Remover

SECTION 5 – FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media Recommendations

Recommended: alcohol resistant foam, CO2, powders, water spray. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions

Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Spill

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

SECTION 7 – HANDLING AND STORAGE

Handling Do not get in eyes, on skin, or on clothing. Keep container tightly closed

when not in use. Wear personal protection equipment. Do not breathe

vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty

containers. Avoid breathing vapors or spray mist.

Storage Keep away from heat, sparks, open flames and oxidizing agents. Keep containers

closed. Store in a cool, dry place with adequate ventilation.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION





TURBO Paint Remover

Engineering Measures Provide forced air ventilation when applying in confined spaces. Respiratory Protection Unlikely to be necessary. Use approved chemical filter respirator.

Safety glasses or chemical eye goggles are suggested. Eyes

Hands Non-natural, non-butyl rubber gloves are recommended.

Skin Use protective clothing. Remove contaminated clothing and wash the affected

with soap and water.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State Viscous liquid

Color clear

Odor a solvent smell **Specific Gravity** 1.40 - 1.50

Viscosity

Solubility in Water Soluble

SECTION 10 – STABILITY AND REACTIVITY

Stability Stable under recommended storage and handling conditions (see section 7).

Hazardous Decomposition Products carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Strong exothermic reactions oxidizing agents, strong alkalis, strong acids.

SECTION 11 – TOXICOLOGICAL INFORMATION

Not Available

SECTION 12 – ECOLOGICAL INFORMATION

Prolonged or repeated contact may cause chronic dermatitis. Appreciable evaporation to air is expected in the environment.

SECTION 13 – DISPOSAL CONSIDERATIONS





TURBO Paint Remover

Method of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14 – TRANSPORT INFORMATION

Proper shipping name Paint
Packing Group III
Hazard Class 3
UN No. 1263

SECTION 15 – REGULATORY INFORMATION

Highly flammable
Harmful by inhalation, in contact with skin and if swallowed
Irritating to eye and skin
Keep out of reach of children
Keep away from sources of ignition – No Smoking
Do not breathe gas/fumes/vapour/spray
Avoid contact with skin and eyes
Wear suitable protective clothing, gloves and eye/face protection

SECTION 16 – OTHER INFORMATION

This document could not be used for certifying the quality of the product.

This document presents the information of the product and to be used for safety only.

Remark The above information and data given here is based on test, experiences that

are considered reliable and believed to be accurate. For more information,

please contact R&D department of NDW Co., Ltd.

reen Industry
กระทรวงอุตสาหกรรม

