




พู่กักร้อปอิน SANKO (CR 3)

ขนาด	เส้นผ่านศูนย์กลาง		ความยาว		กล่องละ	ลังละ	ราคาตัวละ
	ปลั๊ก	เกลียว	ปลั๊ก	ส่วน			
5/16" CT -2530	w5/16"	10.0	30.0	10.5	100	1,000	6.60
3/8" CT -3040	w3/8"	12.0	40.0	15.0	50	1,000	7.15
1/2" CT -4050	w1/2"	16.0	50.0	20.0	50	500	13.20
5/8" CT -5060	w5/8"	21.0	60.0	25.0	25	250	55.00
8 mm CT -830	8	10.0	30.0	10.5	100	1,000	7.70
10 mm CT -1040	10	12.0	40.0	15.0	50	1,000	8.25
12 mm CT -1250	12	16.0	50.0	20.0	50	500	14.30
16 mm CT -1660	16	21.0	60.0	25.0	25	250	63.80


เหล็กตั้ง (Setting Tool) SANKO

ขนาด	ลังละ	ราคาต่อตัว
5/16" HT-2530	20	170.50
3/8" HT-3040, 3030	20	170.50
1/2" HT-4050, 1250	20	209.00
10 mm HT-M10	10	291.50
12 mm HT-M12	10	341.00
16 mm HT-M16	10	396.00


พู่กักรเชื่อม SANKO (WELD ANCHOR)

ขนาด	d	ความลึกรูเจาะ	กล่องละ	ลังละ	ราคาตัวละ
HAS-1040	10	30	100	600	7.70
HAS-1045	10	30	100	600	7.98
HAS-1050	10	40	100	600	8.25
HAS-1055	10	40	100	600	8.53
HAS-1060	10	40	100	600	8.80

**พู่กักร BA - SANKO (BOLT ANCHOR) (CR 3)**

ขนาด	d	D	L	(L)	Drill Dai (O)	Shear Load	Pull Out Figures		บรรจุกล่องละ	บรรจุลังละ	ราคาต่อตัว
							Initial	Ultimate			
BA-1070	10	14.0	70	40	14.5	1820	895	1797	50	300	24.20
BA-1080	10	14.0	80	40	14.5	1820	895	1797	50	200	25.30
BA-1010	10	14.0	100	40	14.5	1820	895	1797	50	200	26.95
BA-1012	10	14.0	120	40	14.5	1820	895	1797	50	200	33.00
BA-1210	12	17.3	100	50	18.0	2750	1150	2822	30	120	42.90
BA-1212	12	17.3	120	50	18.0	2750	1150	2822	30	120	46.20
BA-1215	12	17.3	150	50	18.0	2750	1150	2822	30	100	52.80
BA-1610	16	21.7	100	50	22.0	4820	1610	3705	30	60	77.00
BA-1612	16	21.7	120	60	22.0	4820	1610	3705	30	60	84.70
BA-1615	16	21.7	150	60	22.0	4820	1610	3705	30	60	92.40
H.D.G. BA-1210D	12	17.3	100	50	18.0	2750	1150	2822	30	120	55.00
BA-1612D	16	21.7	120	60	22.0	4820	1610	3705	30	60	110.00


พู่กักร SANKO

ขนาด	d	D	ความยาว		แรงดึง (Kgf)	ความลึก รูดคอนกรีต	บรรจุกล่องละ	บรรจุลังละ	ราคาตัวละ
			L	I					
5/16" GA-25	w5/16"	12	35	13	1,300	35.0	100	800	10.45
3/8" GA-30	w3/8"	14	40	17	1,520	40.0	100	800	12.10
1/2" GA-40	w1/2"	17.3	50	20	2,285	50.0	50	400	18.70
8 mm GA-8M	8	12	35	13	1,300	35.0	100	800	10.45
10 mm GA-10M	10	14	40	17	1,520	40.0	100	800	12.10
12 mm GA-12M	12	17.3	50	20	2,285	50.0	50	400	18.70


พู่กักร SANKO - GT

ขนาด	ลำตัว	ยาว	เกลียว	ส่วน	ความแข็ง คอนกรีต Kgf	รูลึก	บรรจุกล่องละ	บรรจุลังละ	ราคาตัวละ
	mm.	mm.	ยาว	mm.					
3/8" GT-3030	12.0	30.0	12.0	12.5	950.0	30.0	100	800	7.70