

# DUCT TYPE

## AIR CONDITIONING




### DUCT TYPE

MODEL:DHDF / CR



MODEL:DHDF



MODEL:CR



HIGH-POWER AIRFLOW



DURABLE



BLUE FIN



SERVICE VALVE

INDOOR UNIT MODEL			DHDF-18	DHDF-25	DHDF-30	DHDF-30	DHDF-33	DHDF-33	DHDF-36	DHDF-36	DHDF-40	DHDF-40
AIR FLOW	CFM		600	800	1,000	1,000	1,100	1,100	1,200	1,200	1,400	1,400
POWER SUPPLY	V / Ph / Hz		220/1/50									
FAN	TYPE		CENTRIFUGUL DOUBLE INLET , DOUBLE WIDTH									
	QTY		2	2	2	2	2	2	2	2	2	2
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR									
	QTY		1	1	1	1	1	1	1	1	1	1
CONNECTION	SUCTION INCH		1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID INCH		1/4	1/4	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH CM		102.60	115.20	115.20	115.20	115.20	115.20	115.20	115.20	115.20	115.20
	HEIGHT CM		30.00	30.00	35.00	35.00	40.00	40.00	40.00	40.00	40.00	40.00
	DEPTH CM		56.40	56.40	61.40	61.40	61.40	61.40	61.40	61.40	61.40	61.40
APPROX WEIGHT	KG		31.00	33.00	35.00	35.00	35.00	35.00	43.00	43.00	48.00	48.00
OUTDOOR UNIT MODEL			CR-18	CR-25	CR-30	CR-30-3	CR-33	CR-33-3	CR-36	CR-36-3	CR-40	CR-40-3
COOLING CAPACITY	BTU/HR.		18,100	25,000	30,000	30,000	32,400	32,400	36,200	36,200	40,300	40,300
	WATT		5,300	7,300	8,800	8,800	9,500	9,500	10,600	10,600	11,800	11,800
POWER INPUT	WATT		1,710	2,350	2,840	2,840	3,060	3,060	3,420	3,420	3,810	3,810
EER	BTU/WATT		10.58	10.58	10.58	10.58	10.58	10.58	10.58	10.58	10.58	10.58
COMPRESSOR	TYPE		ROTARY									
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN									
REFRIGERANT	TYPE		R32									
POWER SUPPLY	V / Ph / Hz		220/1/50	220/1/50	220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR									
CONNECTION	SUCTION INCH		1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID INCH		1/4	1/4	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH CM		95.00	95.00	95.00	95.00	95.00	95.00	98.00	98.00	98.00	98.00
	HEIGHT CM		69.50	69.50	69.50	69.50	69.50	69.50	79.50	79.50	79.50	79.50
	DEPTH CM		37.00	37.00	37.00	37.00	37.00	37.00	39.00	39.00	39.00	39.00
APPROX WEIGHT	KG		55.00	56.00	62.00	62.00	62.00	62.00	70.00	70.00	75.00	75.00



Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.  
Specification subject to change without notice.