

DUCT TYPE

AIR CONDITIONING




DUCT TYPE

MODEL:DHDF / CR



MODEL:DHDF



MODEL:CR



โทร 1526-2561



HIGH-POWER AIRFLOW



DURABLE



BLUE FIN



SERVICE VALVE



PHASE PROTECTION

INDOOR UNIT MODEL			DHDF-45	DHDF-48	DHDF-60
AIR FLOW	CFM		1,600	1,600	2,000
POWER SUPPLY	V / Ph / Hz		220/1/50		
FAN	TYPE		CENTRIFUGUL DOUBLE INLET , DOUBLE WIDTH		
	QTY		2	2	2
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR		
	QTY		1	1	1
CONNECTION	SUCTION	INCH	5/8	5/8	3/4
	LIQUID	INCH	3/8	3/8	3/8
DIMENSION	WIDTH	CM	115.20	115.20	115.20
	HEIGHT	CM	40.00	40.00	40.00
	DEPTH	CM	61.40	61.40	61.40
APPROX WEIGHT	KG		48	48	50
OUTDOOR UNIT MODEL			CR-45	CR-48	CR-60
COOLING CAPACITY	BTU/HR.		45,000	48,000	60,900
	WATT		13,200	14,100	17,600
POWER INPUT	WATT		4,400	4,700	6,160
EER	BTU/WATT		10.24	10.24	9.89
COMPRESSOR	TYPE		SCROLL		
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN		
REFRIGERANT	TYPE		R32		
POWER SUPPLY	V / Ph / Hz		380/3/50		
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR		
CONNECTION	SUCTION	INCH	5/8	5/8	3/4
	LIQUID	INCH	3/8	3/8	3/8
DIMENSION	WIDTH	CM	110.00	110.00	110.00
	HEIGHT	CM	110.50	110.50	110.50
	DEPTH	CM	40.00	40.00	40.00
APPROX WEIGHT	KG		85.00	85.00	95.00



โทร 1526-2561



TUV NORD Thailand Ltd



TUV NORD Thailand Ltd



TUV NORD Thailand Ltd



SOCOTEC



บริษัท สยามแอร์คอนดิชั่น จำกัด



NSC-11815 17825



Made in Thailand



THAILAND TRUSTED QUALITY



Copyright © 2019

Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit. Specification subject to change without notice.