




LED Downlight Circle

Toshiba LED Downlight elegant with compact design, Fully brightness 100% front lighting performance, good quality material, advantage cooling system, more safety with driver connected with wire, friendly eye care and efficiency brightness for you.

DIMENSION



EQUIVALENT

40W/60W/75W/100W/100W/125W



6W/9W/12W / 15W / 18W / 20W

Compare to Incandescent lamp with conventional fixture

ENERGY SAVING



ENERGY SAVING
85%/85%/84%/85%/84%/85%
SAVES MONEY



มอก. 1955-2551

Non-dimmable

Product code	Voltage (V)	Rated Wattage (W)	Luminous Flux (lm)	Efficacy (lm/W)	Colour Temperature	Color Rendering Index (Ra)	Power Factor	Beam Angle	Lifespan (Hrs.)
RLDDRC00630CTH2	220-240	6	420	70	3000K	>80	>0.5	120°	25,000
RLDDRC00640CTH2	220-240	6	450	75	4000K	>80	>0.5	120°	25,000
RLDDRC00665CTH2	220-240	6	450	75	6500K	>80	>0.5	120°	25,000
RLDDRC00930CTH2	220-240	9	700	78	3000K	>80	>0.5	120°	25,000
RLDDRC00940CTH2	220-240	9	750	83	4000K	>80	>0.5	120°	25,000
RLDDRC00965CTH2	220-240	9	750	83	6500K	>80	>0.5	120°	25,000
RLDDRC01230CTH2	220-240	12	1000	83	3000K	>80	>0.5	120°	25,000
RLDDRC01240CTH2	220-240	12	1080	90	4000K	>80	>0.5	120°	25,000
RLDDRC01265CTH2	220-240	12	1080	90	6500K	>80	>0.5	120°	25,000
RLDDRC01530CTH2	220-240	15	1400	93	3000K	>80	>0.5	120°	25,000
RLDDRC01540CTH2	220-240	15	1500	100	4000K	>80	>0.5	120°	25,000
RLDDRC01565CTH2	220-240	15	1500	100	6500K	>80	>0.5	120°	25,000
RLDDRC01830CTH2	220-240	18	1680	93	3000K	>80	>0.5	120°	25,000
RLDDRC01840CTH2	220-240	18	1800	100	4000K	>80	>0.5	120°	25,000
RLDDRC01865CTH2	220-240	18	1800	100	6500K	>80	>0.5	120°	25,000
RLDDRC02030CTH2	220-240	20	1950	98	3000K	>80	>0.5	120°	25,000
RLDDRC02040CTH2	220-240	20	2100	105	4000K	>80	>0.5	120°	25,000
RLDDRC02065CTH2	220-240	20	2100	105	6500K	>80	>0.5	120°	25,000

*Operation temperature : -20°C to 40°C