




LED Tube T8



Dimension



(mm)

Socket



T8



Beam Angle



TIS1955-2551



Indoor use only

Voltage
(V)

Wattage
(W)

Luminous
Flux (lm)

Efficacy
(lm/W)

Color Temp.
(K)

CRI
(Ra)

Power
Factor

Beam Angle
(°)

Lifetime
(hrs.)

Operation
Temperature (°C)

2ft (600 mm.)										
LED Tube T8 9W	180-260	9	900	100	6,500	70	>0.5	203	15,000	-20~40°C
4ft (1,200 mm.)										
LED Tube T8 18W	180-260	18	1,800	100	6,500	70	>0.5	203	15,000	-20~40°C

PRODUCT FEATURES


- ➔ Easy installation, just replace fluorescent lamp (G13)
- ➔ Save energy up to 65%*
- ➔ Lifetime 15,000 hrs.
- ➔ Environmentally friendly (no mercury, no UV)
- ➔ Indoor use only

* Compare to original fluorescent lamp *

LED Tube T8 full set



Dimension



(mm)



Beam Angle



TIS1955-2551



Indoor use only

Voltage
(V)

Wattage
(W)

Luminous
Flux (lm)

Efficacy
(lm/W)

Color Temp.
(K)

CRI
(Ra)

Power
Factor

Beam Angle
(°)

Lifetime
(hrs.)

Operation
Temperature (°C)

2ft (600 mm.)										
LED Tube T8 full set 9W	180-260	9	900	100	6,500	70	>0.5	203	15,000	-20~40°C
4ft (1,200 mm.)										
LED Tube T8 full set 18W	180-260	18	1,800	100	6,500	70	>0.5	203	15,000	-20~40°C

PRODUCT FEATURES

- ➔ New install instead fluorescent lamp fixture
- ➔ Save energy up to 65%*
- ➔ Lifetime 15,000 hrs.
- ➔ Environmentally friendly (no mercury, no UV)
- ➔ Indoor use only

* Compare to original fluorescent lamp *

Thai Toshiba Lighting Co., Ltd.

144 Moo 5 Bangkadi Industrial Park, Tambon Bangkadi, Amphur Muang, Pathumthani 12000
Tel. +66(0) 2 501 1425-9, 019 6102-5 Fax. +66(0) 2 501 1431, 019 6109

สว่างกลางใจ ไทยทุกดวง

www.toshibalight.com