



LED Spotlight


LED Spotlight provide artificial light with beam angle of 38 degrees. The innovative design allows the outer ring to be fitted and attached to the ceiling. It can be easily adjusted to illuminate any area or object with excellent efficiency.



Round Type

Square Type

DIMENSION



(mm)

EQUIVALENT



Compare to Halogen lamp

ENERGY SAVING



angle adjustable



RoHS 1965-2551



Non-DIMMABLE



Surge Protection

Product code	Voltage (V)	Rated Wattage (W)	Luminous Flux (lm)	Efficacy (lm/W)	Colour Temperature	Color Rendering Index (Ra)	Power Factor	Beam Angle	Lifespan (Hrs.)
LCSC00727WTH1RO	220-240	7	560	80	2700K	≥80	>0.5	38°	20,000h
LCSC00740WTH1RO	220-240	7	560	80	4000K	≥80	>0.5	38°	20,000h
LCSC00765WTH1RO	220-240	7	560	80	6500K	≥80	>0.5	38°	20,000h
LCSC00727WTH1SQ	220-240	7	560	80	2700K	≥80	>0.5	38°	20,000h
LCSC00740WTH1SQ	220-240	7	560	80	4000K	≥80	>0.5	38°	20,000h
LCSC00765WTH1SQ	220-240	7	560	80	6500K	≥80	>0.5	38°	20,000h

Operation temperature : -15°C to 45°C